



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#). [HERE](#)

Flat-ribbon conductor - VS-ASI-FC-TPE-UL-YE 1000M - 1434662

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



AS-Interface TPE flat conductor with UL in yellow, 2 x 1.5 mm², 1000 m on disposable drum



Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 349307

Technical data

Mechanical characteristics

Number of positions	2
Shielded	No
Type of cable	Flat-ribbon conductor
Cable structure	2x 1.5 mm ²
Duty cycle testing	Flexible cable conduit capable
Length of cable	1000 m

Ambient conditions

Ambient temperature (operation)	-40 °C ... 105 °C (fixed routing)
	-30 °C ... 105 °C (Flexibly installed)
Ambient temperature (assembly)	-30 °C ... 105 °C
Ambient temperature (storage/transport)	-40 °C ... 105 °C

Material data

Outer sheath, material	TPE
External sheath, color	yellow RAL 1021

Electrical characteristics

Rated voltage (III/3)	300 V
Rated surge voltage	2 kV

Flat-ribbon conductor - VS-ASI-FC-TPE-UL-YE 1000M - 1434662

Technical data

Standards and Regulations

Duty cycle testing	Flexible cable conduit capable
--------------------	--------------------------------

Line characteristics

Type of cable	Flat-ribbon conductor
Cable structure	2x 1.5 mm ²
Conductor cross section	1.5 mm ²
AWG signal line	16
Conductor structure signal line	84x 0.15 mm
Core diameter including insulation	2.5 mm
Thickness, insulation	approx. 0.5 mm
Wire colors	brown, blue
External sheath, color	lemon yellow RAL 1012
Insulation resistance	≥ 1 MΩ*km
Conductor resistance	≤ 13.7 Ω/km
Nominal voltage, cable	300 V
Test voltage, cable	2000 V
Outer sheath, material	TPE
Material conductor insulation	TPE
Conductor material	Bare Cu litz wires
Cable weight	64 kg/km
Smallest bending radius, fixed installation	≥ 6 mm (one-time)
Traversing direction	horizontal, above the broadside
Max. bending cycles	8000000
Bending radius	75 mm
Traversing rate	4 m/s
Acceleration	4 m/s ²
Traversing direction	vertical, above the broadside
Max. bending cycles	10000000
Bending radius	50 mm
Special properties	UL-Style 2103
	CSA-File LL55255-42
Flame resistance	UL 1581, Sec. 1061 (Cable Flame)
	IEC 60332-1-2
Halogen-free	no
Resistance to oil	UL 1581, Sec. 480 (60 °C)
Other resistance	UV resistant

Classifications

eCl@ss

eCl@ss 4.0	272607xx
------------	----------

Flat-ribbon conductor - VS-ASI-FC-TPE-UL-YE 1000M - 1434662

Classifications

eCl@ss

eCl@ss 4.1	27260701
eCl@ss 5.0	27062002
eCl@ss 5.1	27062002
eCl@ss 6.0	27062002
eCl@ss 7.0	27062002
eCl@ss 8.0	27061801

ETIM

ETIM 3.0	EC000825
ETIM 4.0	EC000825
ETIM 5.0	EC000830

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

Phoenix Contact 2016 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
AS-Interface TPE flat conductor with UL in yellow, 2 x 1.5 mm ² , 1000 m on disposable drum	1434662	VS-ASI-FC-TPE-UL- YE 1000M	Buy on EAN