



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. [HERE](#)

Panel feed-through - Q 1,5/4FL/24-M20KU-ESA-ASI BK - 1437261

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Panel feed-through with QUICKON fast connection technology, for accommodating one or two AS-i flat conductors, on the rear side with manual solder/slip-on connection 4.8 x 0.8 mm



Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 456821

Technical data

Dimensions

Stripping length of the sheath	40 mm
--------------------------------	-------

Ambient conditions

Ambient temperature (operation)	-25 °C ... 80 °C
Degree of protection	IP65
	IP67

General

Number of positions	4
Overvoltage category	III
Degree of pollution	3
Connection method	QUICKON fast connection

Material

Flammability rating according to UL 94	V0
Contact material	Copper alloy
Contact surface material	Pre-nickel plated and tin-plated
Contact carrier material	PA

Standards and Regulations

Connection in acc. with standard	CUL
----------------------------------	-----

Panel feed-through - Q 1,5/4FL/24-M20KU-ESA-ASI BK - 1437261

Technical data

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Classifications

eCl@ss

eCl@ss 4.0	24190219
eCl@ss 4.1	24190219
eCl@ss 5.0	27400209
eCl@ss 5.1	27400209
eCl@ss 6.0	27400209
eCl@ss 7.0	27440304
eCl@ss 8.0	27440103

ETIM

ETIM 3.0	EC000516
ETIM 4.0	EC000516
ETIM 5.0	EC002061

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

Approvals

Approvals

Approvals

UL Recognized / cUL Recognized / VDE Zeichengenehmigung / EAC / cULus Recognized

Ex Approvals

Approvals submitted

Approval details

Panel feed-through - Q 1,5/4FL/24-M20KU-ESA-ASI BK - 1437261

Approvals

UL Recognized	
Nominal current I _N	15 A
Nominal voltage U _N	250 V

cUL Recognized	
Nominal current I _N	11 A
Nominal voltage U _N	250 V


VDE Zeichengenehmigung	
mm ² /AWG/kcmil	0.75-1.5
Nominal voltage U _N	500 V

EAC

cULus Recognized

Drawings

Dimensional drawing



Phoenix Contact 2016 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
Panel feed-through with QUICKON fast connection technology, for accommodating one or two AS-i flat conductors, on the rear side with manual solder/slip-on connection 4.8 x 0.8 mm	1437261	Q 1,5/4FL/24-M20KU-ESA-ASIBK	Buy on EAN