



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. [HERE](#)

Housing - HC-B 10-TMS-100/O1STM32G-EUA - 1690118


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



HEAVYCON ADVANCE for increased environmental requirements, sleeve housing B10, with screw locking, height 100 mm, with 1x M32 thread, straight cable outlet



Key Commercial Data

| | |
|--------------|---|
| Packing unit | 10 STK |
| GTIN |  4 017918 822347 |

Technical data

Dimensions

| | |
|-------------------------------|--------|
| Height | 100 mm |
| Width | 57 mm |
| Length | 105 mm |
| Length of the assembly cutout | 65 mm |
| Width of the assembly cutout | 35 mm |

Ambient conditions

| | |
|--|-----------------------|
| Degree of protection of housing (IP) | IP66 |
| | IP68 (0.2 bar 24 h) |
| | IP69K |
| Degree of protection of housing (NEMA) | 4 (NEMA 250) |
| | 4X (UL50e / NEMA 250) |
| | 6P (UL50e / NEMA 250) |
| | 12 (UL50e / NEMA 250) |
| Ambient temperature (operation) | -40 °C ... 125 °C |

General

| | |
|------|--|
| Note | For contact inserts HC-B10, BB18, DD42, M, K8/24 |
|------|--|

Housing - HC-B 10-TMS-100/O1STM32G-EUA - 1690118

Technical data

General

| | |
|------------------------------|---|
| Size | B10 |
| Housing type | Sleeve housing |
| Locking type | Screw locking |
| Torque | 3 Nm (Locking screw) |
| Fixing screws | M6 |
| No. of cable outlets | 1 |
| Cable exit | straight |
| Screw connection | none |
| Type of the screw connection | 1x M32 |
| Housing material | Die-cast aluminum, salt water resistant |
| Housing surface material | Powder-coated, black |
| Seal material | Viton |
| Material lock | Stainless steel |
| Assembly instructions | In order to guarantee that the ground conductor contact functions even when plugged in at an angle, the two panel mounting flanges must have sufficient electrical contact with the metal mounting panel. |
| Connection | Tightening torque of locking screw: 3 Nm. |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27140816 |
| eCl@ss 4.1 | 27140816 |
| eCl@ss 5.0 | 27371205 |
| eCl@ss 5.1 | 27371205 |
| eCl@ss 6.0 | 27371205 |
| eCl@ss 7.0 | 27371205 |
| eCl@ss 8.0 | 27440202 |
| eCl@ss 9.0 | 27440202 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC000437 |
| ETIM 3.0 | EC000437 |
| ETIM 4.0 | EC000437 |
| ETIM 5.0 | EC000437 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 31261502 |
| UNSPSC 7.0901 | 31261502 |
| UNSPSC 11 | 31261502 |
| UNSPSC 12.01 | 31261502 |
| UNSPSC 13.2 | 31261502 |

Housing - HC-B 10-TMS-100/O1STM32G-EUA - 1690118

Approvals

Approvals

Approvals

EAC / GL

Ex Approvals

Approvals submitted


Approval details

| |
|-----|
| EAC |
|-----|


| |
|----|
| GL |
|----|

Drawings

Dimensional drawing



Dimensional drawing



Panel cutout

²⁾ When self-tapping screws are used (Torx® 20, M4)

Phoenix Contact 2016 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

| Product | Code | Reference | Product link |
|---|---------|------------------------------|----------------------------|
| HEAVYCON ADVANCE for increased environmental requirements, sleeve housing B10, with screw locking, height 100 mm, with 1x M32 thread, straight cable outlet | 1690118 | HC-B 10-TMS-100/O1STM32G-EUA | Buy on EAN |