



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#). [HERE](#)

Protocol converter - RESYGATE 3000 - 2400129

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Protocol converter for up to 4000 PV (process variables) for converting serial communication to Ethernet-based communication for modernizing or combining networks.

Product Description

Resygate 3000 is a protocol converter for up to 4000 PV (process variables). It converts serial and/or TCP-based remote control protocols into standard IEC 60870-5-104 and IEC 60870-5-101 Balanced protocols. Resygate functions as a universal protocol converter with network-capable process connection. In addition, it can be used as a protocol converter or substation for network-isolated connections between control systems.

Why buy this product

- Protocol converter for 4000 process variables
- 3 serial interfaces
- Converts the protocols IEC 60870-5-104, IEC 60870-5-101, Modbus/RTU, Modbus/TCP to IEC 60870-5-104 or IEC 60870-5-101
- Connection of stations via GSM or UMTS
- Connect up to 18 serial terminal devices (depending on protocol)
- Configure local stations easily using pre-installed software with automatic plausibility check
- Use IP address ranges more effectively by forming sub-networks
- Fail-safe thanks to four-fold software redundancy (one converter, four different control systems)

Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 956215

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Display

Display	without display
Resolution	-
Backlighting	without
Touch screen	without

Computer data

Processor	Intel® Celeron® N2930 1.83 GHz/2.16 GHz
-----------	---

Protocol converter - RESYGATE 3000 - 2400129

Technical data

Computer data

Processor fan	without fan
Operating systems	Linux
RAM	2 GB DDR3 SODIMM
Mass storage	4 GB CFast® card
Network	2x Ethernet (10/100/1000 Mbps), RJ45
Network chipset	Intel® 82573L
Interfaces	1x COM (RS-232/422/485)
	2x COM (RS-232)
	3x USB 2.0
	1x USB 3.0
Monitor output	2x DisplayPort
Slots	without slots
Supported remote control protocols	IEC 60870-5-101 Balanced Mode
	IEC 60870-5-101 Unbalanced Mode
	IEC 60870-5-104 Client
	IEC 60870-5-104 Server, max. 4 Client
	Modbus RTU Master
	Modbus TCP Master
Optical drive	Without drive
Realtime clock	Yes (battery-backed)
Service life of battery	5 years (typical)

General

Mounting type	DIN rail mounting
Weight	1.4 kg

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C
Permissible humidity (operation)	5 % ... 95 % (non-condensing)
Permissible humidity (storage/transport)	5 % ... 95 % (non-condensing)
Vibration (operation)	DIN EN 60068-2-6
Shock	15g, 11 ms in accordance with IEC 60068-2-27

Device supply

Power consumption	typical
Power supply unit	24 V DC ±20 %

Standards and Regulations

Shock	15g, 11 ms in accordance with IEC 60068-2-27
Vibration (operation)	DIN EN 60068-2-6

Protocol converter - RESYGATE 3000 - 2400129

Classifications

eCl@ss

eCl@ss 5.1	27240601
eCl@ss 6.0	27259205
eCl@ss 8.0	27242301
eCl@ss 9.0	19200103

ETIM

ETIM 4.0	EC001414
ETIM 5.0	EC001414

Approvals

Approvals

Approvals

UL Listed / cUL Listed / cULus Listed

Ex Approvals

Approvals submitted

Approval details

UL Listed

cUL Listed

cULus Listed

Phoenix Contact 2016 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



Automatización Eléctrica
Especialistas en Automatización

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
Protocol converter for up to 4000 PV (process variables) for converting serial communication to Ethernet-based communication for modernizing or combining networks.	2400129	RESYGATE 3000	Buy on EAN