



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#). [HERE](#)

FO converters - IBS OPTOSUB-MA/M/L-LK-OPC-2MBD - 2740737

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

INTERBUS fiber optic converter for converting the remote OUT interface to fiber optics, correction of the optical transmission capacity, transmission speed of 2 Mbaud, FO output left



Product Description

Modules IBS OPTOSUB-MA/M/L-LK-OPC (-500KBD and -2MBD) convert the INTERBUS remote interface to polymer fiber. Using this converter, you can equip an INTERBUS controller board with an FO interface. Contrary to other converters, this interface is able to regulate the optical signals automatically and is better able to perform diagnostics on the bus line (optical path diagnostics). The converter is a bus device, since it is fitted with an INTERBUS protocol chip (OPC).

Key Commercial Data

Packing unit	1 STK
GTIN	 4 017918 599119

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

Width	65 mm
Height	16 mm
Depth	59 mm

Ambient conditions

Degree of protection	IP20
----------------------	------

General

Net weight	48.04 g
Color	green

Serial interface

Interface	Incoming remote bus
Connection method	D-SUB-9 plug
Transmission length	35 m (50 m system without optical path diagnostics)
	50 m (70 m system with optical path diagnostics)

FO converters - IBS OPTOSUB-MA/M/L-LK-OPC-2MBD - 2740737

Technical data

Optical interface FO

Wavelength	660 nm
Transmission medium	FO
Connection method	F-SMA

Standards and Regulations

Connection in acc. with standard	CUL
----------------------------------	-----

Classifications

eCl@ss

eCl@ss 4.0	27250281
eCl@ss 4.1	27250281
eCl@ss 5.0	27061801
eCl@ss 5.1	27061801
eCl@ss 6.0	27061801
eCl@ss 7.0	27061801
eCl@ss 8.0	27242208

ETIM

ETIM 2.0	EC001467
ETIM 3.0	EC001467
ETIM 4.0	EC001467
ETIM 5.0	EC000310

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	45111807
UNSPSC 11	45111807
UNSPSC 12.01	45111807
UNSPSC 13.2	45111807

Approvals

Approvals

Approvals

UL Recognized / cUL Recognized / cULus Recognized


Ex Approvals


FO converters - IBS OPTOSUB-MA/M/L-LK-OPC-2MBD - 2740737

Approvals

Approvals submitted

Approval details

UL Recognized 

cUL Recognized 

cULus Recognized 

Phoenix Contact 2016 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
INTERBUS fiber optic converter for converting the remote OUT interface to fiber optics, correction of the optical transmission capacity, transmission speed of 2 Mbaud, FO output left	2740737	IBS OPTOSUB-MA/M/L-LK-OPC-2MBD	Buy on EAN