



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#). [HERE](#)

FO cable - PSM-LWL-KDHEAVY-980/1000 - 2744319

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Polymer fiber cable, duplex 980/1000 µm, medium-weight version for permanent indoor installation, by the meter, without connector

Why buy this product

- Universal installation cable for fixed installation indoors
- Rugged polyurethane (PUR) outer sheath
- 2.2 mm individual wires made from extremely hard-wearing polyamide (PA)
- Halogen-free, ozone, and UV resistant

Key Commercial Data

Packing unit	1 M
GTIN	 4 017918 170851

Technical data

Material data

Outer sheath, material	PUR
External sheath, color	red

Ambient conditions

Ambient temperature (operation)	-20 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 80 °C
Altitude	5000 m

Electrical characteristics

Number of positions	2
---------------------	---

Line characteristics

Cable type	Polymer fiber
Cable abbreviation	J-V11Y 4Y2P 980/1000 160A 10
Length of cable	Free input (0.4 ... 100 m)
Wire colors	black/orange
External sheath, color	red
Outer sheath, material	PUR

FO cable - PSM-LWL-KDHEAVY-980/1000 - 2744319

Technical data

Line characteristics

Strain relief elements, external sheath	Non-metallic, aramide fiber
Cable weight	33 kg/km
Bending radius, single element	30 mm (Short-term)
	30 mm (Permanent)
Bending radius, entire cable	30 mm (Short-term)
	30 mm (Permanent)
Tensile strength short-term/long-term	600 N / 100 N
Lateral pressure short term	200 N/cm
Lateral pressure, long-term	20 N/cm
Impact strength	2 Nm / 10 x
cable layer type	Indoors
Halogen-free	According to IEC 60754-2
Fiber	Polymer fiber, 980/1000 µm

Attenuation

660 nm	230 dB/km
--------	-----------

Standards and Regulations

Impact strength	2 Nm / 10 x
Halogen-free	According to IEC 60754-2

Classifications

eCl@ss

eCl@ss 4.0	27061001
eCl@ss 4.1	27061001
eCl@ss 5.0	27061803
eCl@ss 5.1	27061803
eCl@ss 6.0	27061803
eCl@ss 7.0	27061803
eCl@ss 8.0	27061803

ETIM

ETIM 2.0	EC000034
ETIM 3.0	EC000034
ETIM 4.0	EC000034
ETIM 5.0	EC000034

UNSPSC

UNSPSC 6.01	26121607
UNSPSC 7.0901	26121607
UNSPSC 11	26121607

FO cable - PSM-LWL-KDHEAVY-980/1000 - 2744319

Classifications

UNSPSC

UNSPSC 12.01	26121607
UNSPSC 13.2	26121607

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approvals submitted

Approval details

EAC

Phoenix Contact 2016 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
Polymer fiber cable, duplex 980/1000 μ m, medium-weight version for permanent indoor installation, by the meter, without connector	2744319	PSM-LWL-KDHEAVY-980/1000	Buy on EAN