



**Automatización Eléctrica**  
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#). [HERE](#)

## FO cable - PSM-LWL-RUGGED-FLEX-980/1000 - 2744335

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Polymer fiber cable, duplex 980/1000 µm, heavy-weight, highly flexible version for flexible conduit applications, by the meter, without connector

### Why buy this product

- Rugged polyurethane (PUR) outer sheath
- Designed for an alternating bending frequency of up to 5,000,000 cycles
- 2.2 mm individual wires made from extremely hard-wearing polyamide (PA)
- Highly flexible round cable for use in trailing cables or drag chains
- Halogen-free, ozone, and UV resistant

### Key Commercial Data

Packing unit	1 M
GTIN	 4 017918 170837

### Technical data

#### Mechanical characteristics

Number of positions	2
Fiber	Polymer fiber, 980/1000 µm
Cable diameter	8 mm
Duty cycle testing	5 000 000 cycles

#### Ambient conditions

Ambient temperature (operation)	-20 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 80 °C
Altitude	5000 m

#### Material data

Outer sheath, material	PUR
External sheath, color	red

#### Electrical characteristics

Number of positions	2
---------------------	---

#### Line characteristics

# FO cable - PSM-LWL-RUGGED-FLEX-980/1000 - 2744335

## Technical data

### Line characteristics

Cable type	Polymer fiber
Cable abbreviation	J-V11Y 4Y2P 980/1000 180A 10
Length of cable	Free input (0.4 ... 100 m)
External cable diameter	8 mm
Wire colors	black/orange
External sheath, color	red
Outer sheath, material	PUR
Strain relief elements, external sheath	Non-metallic, aramide fiber
Cable weight	54 kg/km
Bending radius, single element	30 mm (Short-term)
	30 mm (Permanent)
Bending radius, entire cable	50 mm (Short-term)
	50 mm (Permanent)
Tensile strength short-term/long-term	200 N / 100 N
Lateral pressure short term	300 N/cm
Lateral pressure, long-term	20 N/cm
Impact strength	2 Nm / 10 x
cable layer type	Indoors
Halogen-free	According to IEC 60754-2
Fiber	Polymer fiber, 980/1000 µm

### Attenuation

660 nm	275 dB/km
--------	-----------

### Standards and Regulations

Duty cycle testing	5 000 000 cycles
Impact strength	2 Nm / 10 x
Halogen-free	According to IEC 60754-2

## Classifications

### eCl@ss

eCl@ss 4.0	27061001
eCl@ss 4.1	27061001
eCl@ss 5.0	27061803
eCl@ss 5.1	27061803
eCl@ss 6.0	27061803
eCl@ss 7.0	27061803
eCl@ss 8.0	27061803

### ETIM

ETIM 2.0	EC000034
----------	----------

# FO cable - PSM-LWL-RUGGED-FLEX-980/1000 - 2744335

## Classifications

### ETIM

ETIM 3.0	EC000034
ETIM 4.0	EC000034
ETIM 5.0	EC000034

### UNSPSC

UNSPSC 6.01	26121607
UNSPSC 7.0901	26121607
UNSPSC 11	26121607
UNSPSC 12.01	26121607
UNSPSC 13.2	26121607

## Approvals

### Approvals

---

Approvals

EAC

---

Ex Approvals

---

Approvals submitted

---

### Approval details

EAC
-----

---

Phoenix Contact 2016 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

<b>Product</b>	<b>Code</b>	<b>Reference</b>	<b>Product link</b>
Polymer fiber cable, duplex 980/1000 $\mu$ m, heavy-weight, highly flexible version for flexible conduit applications, by the meter, without connector	2744335	PSM-LWL-RUGGED-FLEX-980/1000	<a href="#">Buy on EAN</a>