



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#). [HERE](#)

Distributed I/O device - FLX ASI DO 4 M12-2A - 2773458

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



AS-i digital output module, single slave, 4 digital outputs, 24 V DC, IP67 protection

Product Description

The digital Fieldline M12 AS-Interface output modules with IP67 housing protection make it possible to connect digital actuators to the AS-i using M12 plugs using the SPEEDCON connection method.

The modules are connected to AS-i using the flat-ribbon cable cable penetration technique.

Why buy this product

- Tool-free connection to AS-Interface using penetration technique
- M12 connection technology with SPEEDCON fast locking system for the I/Os
- Optimized for direct mounting and DIN rail mounting



Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 156578

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

Width	58 mm
Height	118 mm
Depth	35 mm
Drill hole spacing	108 mm

Ambient conditions

Ambient temperature (operation)	-25 °C ... 70 °C
Ambient temperature (storage/transport)	-25 °C ... 85 °C
Degree of protection	IP65/IP67

Distributed I/O device - FLX ASI DO 4 M12-2A - 2773458

Technical data

Interfaces

Fieldbus system	AS-i
Designation	AS-Interface
Connection method	Flat-ribbon cable penetration technique
Designation connection point	AS-i
Transmission speed	167 kBit/s
Number of positions	4

AS-Interface

Slave type	Single slave
AS-i specification	2.0
IO code	8
ID code (hex)	1
ID code (dec.)	1
AS-i profile	S-8.1
Required master specification	>= 2.0

Digital outputs

Output name	Digital outputs
Connection method	M12 connector
	2-wire
Number of outputs	4
Maximum output current per channel	2 A
Maximum output current per module / terminal block	4 A

General

Net weight	195 g
Mounting type	Wall mounting
	Screw on directly or on DIN rail

Standards and Regulations

Protection class	III, IEC 61140, EN 61140, VDE 0140-1
------------------	--------------------------------------

Classifications

eCl@ss

eCl@ss 4.0	27250302
eCl@ss 4.1	27250302
eCl@ss 5.0	27250302
eCl@ss 5.1	27242604
eCl@ss 6.0	27242604
eCl@ss 7.0	27242604
eCl@ss 8.0	27242604
eCl@ss 9.0	27242604

Distributed I/O device - FLX ASI DO 4 M12-2A - 2773458

Classifications

ETIM

ETIM 2.0	EC001430
ETIM 3.0	EC001599
ETIM 4.0	EC001599
ETIM 5.0	EC001599

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	43201404

Approvals

Approvals

Approvals

UL Listed / cUL Listed / ASI-Interface / EAC / cULus Listed

Ex Approvals

Approvals submitted

Approval details

UL Listed

cUL Listed

ASI-Interface

EAC


Distributed I/O device - FLX ASI DO 4 M12-2A - 2773458

Approvals

cULus Listed

Drawings

Connection diagram



Phoenix Contact 2016 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



Automatización Eléctrica
Especialistas en Automatización

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
AS-i digital output module, single slave, 4 digital outputs, 24 V DC, IP67 protection	2773458	FLX ASI DO 4 M12-2A	Buy on EAN