



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. [HERE](#)

AS-i gateway - FLX ASI MA PB SF - 2773597

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



AS Interface (AS-i) Gateway for PROFIBUS DP with standard function, IP20 degree of protection, as per AS-i specification 3.0

Product Description

The Fieldline Extension AS-Interface gateway for PROFIBUS DP FLX ASI MA PB SF enables the simple integration of an AS-Interface network in a PROFIBUS DP system. The device has a rugged, high-grade steel housing with the IP20 degree of protection, and is intended for use in the control cabinet.

The gateway enables the operation of AS-Interface slaves with expanded addressing and is specified according to the AS-Interface specification 3.0.

The downward compatibility with AS-i slaves of older specifications is also given.

The connected AS-i slaves can be easily addressed through the AS-Interface gateway using the "Mode" and "Set" keys as well as a 7-segment display.

Why buy this product

- For one or two AS-Interface networks
- Stainless steel housing
- AS-Interface specification 3.0
- IP20 degree of protection



Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 436038

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

Width	45 mm
Height	120 mm

AS-i gateway - FLX ASI MA PB SF - 2773597

Technical data

Dimensions

Depth	44 mm
-------	-------

Ambient conditions

Ambient temperature (operation)	0 °C ... 55 °C
Ambient temperature (storage/transport)	-25 °C ... 85 °C
Degree of protection	IP20

Interfaces

Interface	PROFIBUS DP remote bus
Connection method	1x D-SUB-9 connector

Power supply

Typical current consumption	approx. 200 mA (from the AS-i network)
-----------------------------	--

Operating elements

Keys	2 buttons (Mode/Set) for configuring the AS-i network
Number of AS-i slaves	62
Local diagnostics	Addresses, error messages 7-segment display
	power Operating voltage, electronics module (UL) Green LED
	U AS-i Operating voltage AS-i (U ASI) Green LED
	AS-i active AS-i transmission (ASI ACTIVE) Green LED
	prg enable Programming mode active, automatic slave programming possible Green LED
	prj mode Configuration mode active (PRJ Enable) Yellow LED
	fault AS-i configure error (CONFIG ERR) LED red
	PROFIBUS Device/network status Green LED

General

Weight	300 g
--------	-------

Standards and Regulations

Shock	according to EN 61131-2
-------	-------------------------

Classifications

eCl@ss

eCl@ss 4.0	27240490
eCl@ss 4.1	27240490
eCl@ss 5.0	27242208
eCl@ss 5.1	27242608
eCl@ss 6.0	27242608
eCl@ss 7.0	27242608
eCl@ss 8.0	27242608

AS-i gateway - FLX ASI MA PB SF - 2773597

Classifications

ETIM

ETIM 3.0	EC001604
ETIM 4.0	EC001604
ETIM 5.0	EC001604

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	43201404

Approvals

Approvals

Approvals

UL Listed / cUL Listed / ASI-Interface / EAC / cULus Listed

Ex Approvals

Approvals submitted

Approval details

UL Listed 

cUL Listed 

ASI-Interface


EAC

cULus Listed 

AS-i gateway - FLX ASI MA PB SF - 2773597

Drawings

Dimensional drawing



Phoenix Contact 2016 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
AS Interface (AS-i) Gateway for PROFIBUS DP with standard function, IP20 degree of protection, as per AS-i specification 3.0	2773597	FLX ASI MA PB SF	Buy on EAN