



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#). [HERE](#)

Surge protection device - TT-SLKK5/ 60AC - 2794974

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Modular terminal block with varistor as surge voltage protection between clamping connector and DIN rail, separate ground connection, nominal voltage: 60 V AC, mounting on NS 35/7.5, terminal width: 6.2 mm, terminal height: 69 mm

The illustration shows version TT-SLKK5/ 12 DC

Why buy this product

- Modular terminal blocks with screw connection technology
- Protective element between the feed-through terminal block and the metal mounting foot

Key Commercial Data

Packing unit	50 STK
GTIN	 4 017918 073046

Technical data

Dimensions

Height	69.5 mm
Width	6.2 mm
Length	66.5 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
Degree of protection	IP20

General

Housing material	PA
Flammability rating according to UL 94	V2
Color	black
Mounting type	DIN rail: 35 mm
Type	Single-level terminal block – separate PE connection
Number of positions	1
Direction of action	Line-Earth Ground

Protective circuit

IEC test classification	C1
-------------------------	----

Surge protection device - TT-SLKK5/ 60AC - 2794974

Technical data

Protective circuit

	C2
	C3
VDE requirement class	C1
	C2
	C3
Nominal voltage U_N	60 V AC
Maximum continuous voltage U_C	100 V DC
	75 V AC
Maximum continuous voltage U_C (wire-ground)	100 V DC
	75 V AC
Nominal current I_N	32 A (50 °C)
Operating effective current I_C at U_C	$\leq 50 \mu\text{A}$
Residual current I_{PE}	$\leq 50 \mu\text{A}$
Nominal discharge current I_n (8/20) μs (Core-Earth)	2 kA
Total surge current (8/20) μs	6.5 kA
Max. discharge current I_{max} (8/20) μs maximum (Core-Earth)	6.5 kA
Nominal pulse current I_{an} (10/1000) μs (Core-Earth)	75 A
Output voltage limitation at 1 kV/ μs (Core-Earth) spike	$\leq 180 \text{ V}$
Output voltage limitation at 1 kV/ μs (Core-Earth) static	$\leq 180 \text{ V}$
Residual voltage at I_n (conductor-ground)	$\leq 315 \text{ V}$
Response time t_A (Core-Earth)	$\leq 25 \text{ ns}$
Cut-off frequency f_g (3 dB), asym. (PE) in 150 Ohm system	typ. 1.1 MHz

Connection data

Connection method	Screw connection
Connection type IN	Screw terminal blocks
Connection type OUT	Screw terminal blocks
Screw thread	M3
Tightening torque	0.5 Nm
Stripping length	8 mm
Conductor cross section flexible min.	0.2 mm ²
Conductor cross section flexible max.	4 mm ²
Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	4 mm ²
Conductor cross section AWG min.	24
Conductor cross section AWG max.	12

Standards and Regulations

Standards/regulations	IEC 61643-21
-----------------------	--------------

Surge protection device - TT-SLKK5/ 60AC - 2794974

Classifications

eCl@ss

eCl@ss 4.0	27140201
eCl@ss 4.1	27130801
eCl@ss 5.0	27130801
eCl@ss 5.1	27130801
eCl@ss 6.0	27130807
eCl@ss 7.0	27130807
eCl@ss 8.0	27130807
eCl@ss 9.0	27130807

ETIM

ETIM 2.0	EC000943
ETIM 3.0	EC000943
ETIM 4.0	EC000943
ETIM 5.0	EC000943

UNSPSC

UNSPSC 6.01	30212010
UNSPSC 7.0901	39121610
UNSPSC 11	39121610
UNSPSC 12.01	39121610
UNSPSC 13.2	39121620

Approvals

Approvals

Approvals

CSA / UL Recognized / cUL Recognized / EAC / EAC / cULus Recognized

Ex Approvals

Approvals submitted

Approval details

Surge protection device - TT-SLKK5/ 60AC - 2794974

Approvals

CSA	
mm ² /AWG/kcmil	28-12
Nominal current I _N	34 A
Nominal voltage U _N	60 V

UL Recognized	
mm ² /AWG/kcmil	26-10
Nominal current I _N	30 A
Nominal voltage U _N	60 V

cUL Recognized	
mm ² /AWG/kcmil	26-12
Nominal current I _N	30 A
Nominal voltage U _N	60 V


EAC

EAC

cULus Recognized

Drawings

Circuit diagram



Phoenix Contact 2016 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
Modular terminal block with varistor as surge voltage protection between clamping connector and DIN rail, separate ground connection, nominal voltage: 60 V AC, mounting on NS 35/7.5, terminal width: 6.2 mm, terminal height: 69 mm	2794974	TT-SLKK5/ 60AC	Buy on EAN