



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#). [HERE](#)

FO cable - PSM-LWL-GDM-RUGGED- 50/125 - 2799322

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Fiberglass cable, duplex 50/125 µm, by the meter, without connector, for indoor installation

The illustration shows version PSM-LWL-PCF-200/230

Why buy this product

- Highly tear-resistant aramid strain relief elements
- Rugged installation cable for indoor use
- Rugged polyurethane (PUR) outer sheath
- 2.9 mm individual wires made from highly flexible FRNC material
- Halogen-free, ozone, and UV resistant

Key Commercial Data

Packing unit	1 M
GTIN	 4 017918 074029

Technical data

Mechanical characteristics

Number of positions	2
Fiber	Fiberglass, 50/125 µm
Cable diameter	8 mm

Ambient conditions

Ambient temperature (operation)	-20 °C ... 70 °C
Ambient temperature (storage/transport)	-25 °C ... 70 °C
Altitude	5000 m

Material data

Outer sheath, material	PUR
External sheath, color	orange

Electrical characteristics

Number of positions	2
---------------------	---

Line characteristics

FO cable - PSM-LWL-GDM-RUGGED- 50/125 - 2799322

Technical data

Line characteristics

Cable type	Multimode fiberglass
Cable abbreviation	I-V(ZN)H11Y 2G50/125 2,5B600+0,7F1200
Length of cable	Free input (1.0 ... 2000 m)
External cable diameter	8 mm
Wire colors	Red/Green
External sheath, color	orange
Outer sheath, material	PUR
Cable weight	50 kg/km
Bending radius, single element	30 mm (Short-term) 50 mm (Permanent)
Bending radius, entire cable	65 mm (Short-term) 65 mm (Permanent)
Tensile strength short-term/long-term	1000 N / 200 N
Lateral pressure short term	400 N/cm
Lateral pressure, long-term	100 N/cm
Impact strength	2 Nm / 10 x
cable layer type	Indoors
Halogen-free	According to IEC 60754-2
Fiber	Fiberglass, 50/125 µm

Attenuation

850 nm	2.5 dB/km
1300 nm	0.7 dB/km

Standards and Regulations

Impact strength	2 Nm / 10 x
Halogen-free	According to IEC 60754-2

Classifications

eCl@ss

eCl@ss 4.0	27061001
eCl@ss 4.1	27061001
eCl@ss 5.0	27061803
eCl@ss 5.1	27061803
eCl@ss 6.0	27061803
eCl@ss 7.0	27061803
eCl@ss 8.0	27061803

ETIM

ETIM 2.0	EC001122
ETIM 3.0	EC001122

FO cable - PSM-LWL-GDM-RUGGED- 50/125 - 2799322

Classifications

ETIM

ETIM 4.0	EC001122
ETIM 5.0	EC000034

UNSPSC

UNSPSC 6.01	26121607
UNSPSC 7.0901	26121607
UNSPSC 11	26121607
UNSPSC 12.01	26121607
UNSPSC 13.2	26121607

Phoenix Contact 2016 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
Fiberglass cable, duplex 50/125 μm , by the meter, without connector, for indoor installation	2799322	PSM-LWL-GDM-RUGGED- 50/125	Buy on EAN