



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#). [HERE](#)

Monitor - VL FPM 15U - 2913018

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



15"/38.1 cm flat panel LCD monitor with resistive touch screen. Includes two rear USB ports and one front USB port.

15-in. display shown

Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 662376

Technical data

Dimensions

Installation dimension, width	386.6 mm
Installation dimension, height	285 mm
Note regarding installation dimension	Panel cutout

Display

Display	38.1 cm/15" TFT
Resolution	1024 x 768 Pixel (XGA)
Backlighting	CCFL
Display backlight MTBF	> 50000 h
Touch screen	Resistive industrial touch screen
Colors	16.2 million colors

Monitor data

Network	Without network
Interfaces	1x USB 1.1, Typ A
	1x USB 2.0, Typ A
	1x USB on front
Monitor output	1x DVI-D
	1x VGA
Slots	without slots

General

Mounting type	Panel cutout or VESA mount
---------------	----------------------------

Monitor - VL FPM 15U - 2913018

Technical data

General

Weight	4.51 kg
--------	---------

Ambient conditions

Degree of protection	IP65 (front), IP20 (back)
Ambient temperature (operation)	0 °C ... 55 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C
Permissible humidity (operation)	5 % ... 95 %
Permissible humidity (storage/transport)	5 % ... 95 %
Vibration (operation)	DIN EN 60068-2-6
Shock	15g, 11 ms in accordance with IEC 60068-2-27

Device supply

Supply voltage	24 V DC (typical)
Supply voltage range	19.2 V DC ... 28.8 V DC
Power supply unit	24 V DC ±20 %

Standards and Regulations

Shock	15g, 11 ms in accordance with IEC 60068-2-27
Vibration (operation)	DIN EN 60068-2-6

Classifications

eCl@ss

eCl@ss 5.1	27242402
eCl@ss 6.0	19200201
eCl@ss 8.0	19200403

ETIM

ETIM 3.0	EC001425
ETIM 4.0	EC001428
ETIM 5.0	EC001428

UNSPSC

UNSPSC 12.01	43211902
--------------	----------



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
15"/38.1 cm flat panel LCD monitor with resistive touch screen. Includes two rear USB ports and one front USB port.	2913018	VL FPM 15U	Buy on EAN