



**Automatización Eléctrica**  
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#). [HERE](#)

## Touch panel - WP 06T - 2913645

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Touch panel with 14.5 cm (5.7") graphics-capable TFT display, 320 x 240 pixels, 1 x Ethernet, 2 x USB, and integrated micro browser

### Why buy this product

- Short startup time
- Easy installation, low installation depth, and compact design
- Low maintenance costs - projects are only adapted once
- Micro browser (WebVisit client) integrated as standard in all devices
- Display available in sizes from 8.9 cm (3.5") to 38.1 cm (15")
- Easy device replacement - the visualization project is saved on the PLC (web server)
- Energy efficient due to LED backlighting

### Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 460491

### Technical data

#### Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

#### Dimensions

External dimension, width	168 mm
External dimension, height	126 mm
External dimension, depth	5 mm
Note regarding external dimension	Dimensions of the front plate
Installation dimension, width	160 mm
Installation dimension, height	118 mm
Installation dimension, depth	42 mm

#### Display

Display	14.5 cm/5.7" TFT active
Resolution	320 x 240 Pixel (QVGA)

# Touch panel - WP 06T - 2913645

## Technical data

### Display

Backlighting	LED
Display backlight MTBF	40000 h
Touch screen	Resistive industrial touch screen
Colors	65536 colors

### Computer data

Processor	ARM9™, 200 MHz
Operating systems	MS Windows® CE 5.0
User software	MicroBrowser
RAM	64 MB SDRAM
Mass storage	32 MByte flash memory
Network	1 x Ethernet (10/100 Mbps), RJ45
Interfaces	2x USB Host 2.0
Bus system	without

### General

Mounting type	Front installation
---------------	--------------------

### Ambient conditions

Degree of protection	IP65 (front), IP20 (back)
Ambient temperature (operation)	0 °C ... 50 °C
Ambient temperature (storage/transport)	-25 °C ... 70 °C
Permissible humidity (operation)	20 % ... 85 % (non-condensing)
Permissible humidity (storage/transport)	10 % ... 95 % (non-condensing)
Vibration (operation)	DIN EN 60068-2-6
Shock	DIN EN 60068-2-27

### Device supply

Power supply unit	24 V DC ±20 %
-------------------	---------------

### Standards and Regulations

Shock	DIN EN 60068-2-27
Vibration (operation)	DIN EN 60068-2-6

## Classifications

### eCl@ss

eCl@ss 5.1	27242302
eCl@ss 6.0	27242302
eCl@ss 8.0	27242302

### ETIM

ETIM 2.0	EC001412
----------	----------

# Touch panel - WP 06T - 2913645

## Classifications

### ETIM

ETIM 3.0	EC001412
ETIM 4.0	EC001412
ETIM 5.0	EC001412

### UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43211903
UNSPSC 13.2	43201404

## Approvals

### Approvals

---

#### Approvals

GL / GL-SW / UL Listed / cUL Listed / DNV / EAC / LR / ABS / RINA / EAC / BV / GL / cULus Listed

---

#### Ex Approvals

---

#### Approvals submitted

---

### Approval details

GL

GL-SW

UL Listed

cUL Listed

DNV

EAC

# Touch panel - WP 06T - 2913645

## Approvals

LR

ABS

RINA

EAC

BV

GL

cULus Listed 

Phoenix Contact 2016 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
Touch panel with 14.5 cm (5.7") graphics-capable TFT display, 320 x 240 pixels, 1 x Ethernet, 2 x USB, and integrated micro browser	2913645	WP 06T	<a href="#">Buy on EAN</a>