



**Automatización Eléctrica**  
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. [HERE](#)

## Electronic housing - ME 35 UT TBUS KMGY - 2914819

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Component housing with vents, Lower part, Cross connection: DIN rail bus connector, Color: light gray, Width: 35 mm, Constructional height: 114.5 mm, Number of positions cross connector: 5

### Why buy this product

- Item is from the ME product range
- Tool-free mounting
- Available in overall widths from 12.5 mm to 90 mm, modular extension is possible
- Inflammability class V0 according to UL 94
- Variety of connection technologies
- Can be mounted on the DIN rail
- Optional bus connector that is either integrated or mounted on the DIN rail

### Key Commercial Data

|              |                     |
|--------------|---------------------|
| Packing unit | 10 STK              |
| GTIN         | <br>4 017918 964634 |

### Technical data

#### General

|                  |                   |
|------------------|-------------------|
| Housing type     | Component housing |
| Housing material | Polyamide         |
| Color            | light gray        |

#### Ambient conditions

|                                 |  |
|---------------------------------|--|
| Ambient temperature (operation) | -40 °C ... 105 °C (depending on power dissipation) |
|---------------------------------|--|

#### Dimensions

|                       |          |
|-----------------------|----------|
| Length                | 99 mm    |
| Constructional height | 114.5 mm |
| Width                 | 35 mm    |

#### Technical data

|  |       |
|--|-------|
| Flammability rating according to UL 94 | V0    |
| Power dissipation without gap          | 7.9 W |

# Electronic housing - ME 35 UT TBUS KMGY - 2914819

## Technical data

### Technical data

|                                  |        |
|----------------------------------|--------|
| Power dissipation with 20 mm gap | 16.3 W |
| Number of positions              | 24     |

### Standards and Regulations

|  |    |
|--|----|
| Flammability rating according to UL 94 | V0 |
|--|----|

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27180401 |
| eCl@ss 4.1 | 27180401 |
| eCl@ss 5.0 | 27180506 |
| eCl@ss 5.1 | 27180506 |
| eCl@ss 6.0 | 27180802 |
| eCl@ss 7.0 | 27182702 |
| eCl@ss 8.0 | 27182702 |
| eCl@ss 9.0 | 27182702 |

### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC001031 |
| ETIM 3.0 | EC001031 |
| ETIM 4.0 | EC001031 |
| ETIM 5.0 | EC001031 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 31261501 |
| UNSPSC 7.0901 | 31261501 |
| UNSPSC 11     | 31261501 |
| UNSPSC 12.01  | 31261501 |
| UNSPSC 13.2   | 31261501 |

## Approvals

### Approvals

---

#### Approvals

UL Recognized

---

#### Ex Approvals

---


## Electronic housing - ME 35 UT TBUS KMGY - 2914819

### Approvals

Approvals submitted

---

#### Approval details

UL Recognized 

---

Phoenix Contact 2016 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

| Product  | Code    | Reference             | Product link               |
|--|---------|-----------------------|----------------------------|
| Component housing with vents, Lower part, Cross connection: DIN rail bus connector, Color: light gray, Width: 35 mm, Constructional height: 114.5 mm, Number of positions cross connector: 5 | 2914819 | ME 35 UT<br>TBUS KMGY | <a href="#">Buy on EAN</a> |