



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. [HERE](#)

Software - VISU+ 2 RT-D 256 - 2988719

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Runtime license for Visu+ where the I/O data and variables in scripting are limited to 256 bytes. 2 direct driver connections are also supported.

Why buy this product

- Full SCADA (Supervisory Control And Data Acquisition) function with visualization, trend representation, and alarm management
- Control coupling with OPC and 2 direct drivers
- Direct driver connection to controllers, e.g., to Siemens S7 or via Modbus/TCP and Modbus/RTU
- Data logging, trend display, and recipe management
- Scripts can be created in VBA and IL
- Fully scalable process diagrams for using one design on different devices and monitor sizes
- Multilingual software and projects, thanks to Unicode support and online selection
- Access protection with user management

VISU+
SCADA Visualization

Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 479752

Technical data

License information

Type of software	Visualization
Type of license	Runtime license

Functions

Number of I/O nodes	256 I/O bytes
Basic functions	Know-How protection and safety through encoding of projects
	Realtime database coupling with ODBC to MS ACCESS, MS EXCEL and SQL server
	FDA CFR 21 Part 11 compatible
Expanded functionality	Statistical alarm function
	Web client capability
	Redundancy function

Software - VISU+ 2 RT-D 256 - 2988719

Technical data

Functions

	Advanced alarm management with SMS, FAX, e-mail and voice mail function
	Networking
	Visu+ as OPC server (DA & XL)

Hardware requirements

Hard disk	min. 1 GByte (Recommended: 2 GB)
CPU	Pentium/Celeron, 1.6 GHz
Optical drive	DVD-ROM
Monitor resolution	XGA (1024 x 768)
Operating equipment	Keyboard, mouse

Software requirements

Operating systems	MS Windows® XP (SP3)
	MS Windows® Vista Business
	MS Windows® 7 Professional (32 bit/64 bit), SP1
	MS Windows® 7 Ultimate (32-Bit/64-Bit), SP1
	MS Windows® 8 Professional (32-Bit/64-Bit)
	MS Windows® 8 Enterprise (32-Bit/64-Bit)
	MS Windows® Server 2003
	MS Windows® Server 2008
	MS Windows® Server 2008 R2
Supported browsers	Internet Explorer 5.5 or higher

Classifications

eCl@ss

eCl@ss 4.0	27248002
eCl@ss 4.1	27248002
eCl@ss 5.0	27242502
eCl@ss 5.1	27242502
eCl@ss 6.0	27242502
eCl@ss 7.0	27242502
eCl@ss 8.0	27242502

ETIM

ETIM 2.0	EC001416
ETIM 3.0	EC001416
ETIM 4.0	EC001416
ETIM 5.0	EC001416

Software - VISU+ 2 RT-D 256 - 2988719

Classifications

UNSPSC

UNSPSC 6.01	43163005
UNSPSC 7.0901	43232404
UNSPSC 11	43163005
UNSPSC 12.01	43232404
UNSPSC 13.2	43232404

Phoenix Contact 2016 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
Runtime license for Visu+ where the I/O data and variables in scripting are limited to 256 bytes. 2 direct driver connections are also supported.	2988719	VISU+ 2 RT-D 256	Buy on EAN