



**Automatización Eléctrica**  
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. [HERE](#)

## Industrial Ethernet Switch - FL NAT SMN 8TX - 2989365

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Smart Managed Narrow NAT switch with eight 10/100 Mbps RJ45 ports and 1:1 NAT router function

NAT switch

### Product Description

#### Description

The FL NAT SMN 8TX is the first product in the range of Phoenix Contact to combine the functions of a NAT router (NAT = Network Address Translation) and a switch in one device. The NAT switch is suitable for all applications in automation applications with a control cabinet friendly, slim housing, the "manual factor".

Port 1 is the port via which the NAT implementation takes place in the higher-level network. Ports 2 to 8 of the managed switch are used for the higher-level network. The FL NAT SMN 8TX can be configured via a web server as well as via SNMP (Simple Network Management Protocol). The FL NAT SMN 8TX is the first combination device that combines switch mechanism (at layer2 level) and routing (at layer3 level). If two devices were needed in the past and thus double installation width for installation and double price for the procurement, FL NAT SMN 8TX is a highly functional device at a highly attractive price.

The switch functions including port mirroring, LLDP or redundancy mechanisms ensure the standard, powerful data communication on seven 100 Mbps LAN ports.

Machine manufacturers always have the problem of fitting their machines with an IP address area which can be integrated back into the IT network of their customers. With the FL NAT SMN 8TX individual machines or systems can be equipped with always identical IP addresses and then these IP addresses in the application are implemented in the required IP address areas of the higher-level company network. This function block is usually known as Network Address Translation - NAT.

#### Why buy this product

- Web-based management, SNMP
- Slim design
- VLANs
- SNMP
- 1:1 NAT
- Virtual NAT
- 7 LAN-Ports
- RSTP with fast switch-over
- Routing

### Ethernet

#### Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 456074

# Industrial Ethernet Switch - FL NAT SMN 8TX - 2989365

## Technical data

### Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---------------------------------------------------------------------------

### Dimensions

Width	58 mm
Height	133 mm
Depth	130 mm

### Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	0 °C ... 55 °C (non-condensing)
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Permissible humidity (operation)	5 % ... 95 % (non-condensing)
Permissible humidity (storage/transport)	5 % ... 95 % (non-condensing)
Air pressure (operation)	86 kPa ... 108 kPa (2000 m above sea level)
Air pressure (storage/transport)	66 kPa ... 108 kPa (3500 m above sea level)

### Interfaces

Interface 1	Ethernet
No. of ports	8 (RJ45 ports)
Connection method	RJ45
Note on connection method	Auto negotiation and autocrossing
Transmission physics	Copper
Transmission speed	10/100 MBit/s
Transmission length	100 m (per segment)
Signal LEDs	Supply voltage, data transmission, error, link, activity
Interface 4	Serial (RS-232)
Connection method	RS-232-C, 6-pos. MINI-DIN socket (PS/2)

### Function

Basic functions	Store and forward switch, complies with IEEE 802.3 2, priority classes in acc. with IEEE 802.1 P TCP/IP protocol, BootP-capable, integrated web server function, Rapid Spanning Tree (RSTP), router, 1:1 NAT router
Management	Web-based management (HTTP)
	SNMP v1/v2
Diagnostic functions	RMON History
	LLDP (Link Layer Discovery Protocol)
	SNMP-Traps
Filter functions	VLAN (up to 32 VLANs)
Supported browsers	Internet Explorer 5.5 or higher
Redundancy	RSTP (Rapid Spanning Tree Protocol)
	FRD (Fast Ring Detection)
	Large Tree Support

# Industrial Ethernet Switch - FL NAT SMN 8TX - 2989365

## Technical data

### Function

	STP (Spanning Tree Protocol)
	MRP (Media Redundancy Protocol)
PROFINET IO conformance class	Conformance-Class A
Additional functions	Routing (1:1 NAT, Virtual NAT, Routing)
	BootP
	DHCP-Client
Status and diagnostic indicators	LEDs: US1, US2 (power supply), Fail (alarm contact), 2 LEDs per Ethernet port (Link and switchable Activity/Speed/Duplex)
Signal contact control voltage	24 V DC (typical)
Signal contact control current	600 mA (maximum)

### Network expansion parameters

Cascading depth	Network, linear, and star structure: any
Maximum conductor length (twisted pair)	100 m

### Supply voltage

Supply voltage	24 V DC (redundant)
Residual ripple	3.6 V <sub>PP</sub> (within the permitted voltage range)
Supply voltage range	18 V DC ... 32 V DC
Typical current consumption	600 mA (at U <sub>S</sub> = 24 V DC)
Max. current consumption	600 mA

### General

Mounting type	DIN rail
Type AX	Book type
Net weight	650 g

### Standards and Regulations

Electromagnetic compatibility	Conformance with EMC Directive 2004/108/EC
Test standard	IEC 61000-4-2 (ESD)
Test result	Criterion A
Test standard	IEC 61000-4-3 (electromagnetic fields)
Test result	Criterion A
Test standard	IEC 61000-4-4 (burst)
Test result	Criterion A
Test standard	IEC 61000-4-5 (surge)
Test result	Criterion A
Test standard	IEC 61000-4-6 (immunity to conducted interference)
Test result	Criterion A
Test section	For one minute 500 V DC
Type of test	Shock in acc. with EN 60068-2-27/IEC 60068-2-27
Test result	Operation: 25g, 11 ms duration, semi-sinusoidal shock impulse
Type of test	Shock in acc. with EN 60068-2-27/IEC 60068-2-27

# Industrial Ethernet Switch - FL NAT SMN 8TX - 2989365

## Technical data

### Standards and Regulations

Test result	Storage/Transport: 50g, 11 ms duration, semi-sinusoidal shock impulse
Type of test	Vibration resistance in acc. with EN 60068-2-6/IEC 60068-2-6
Test result	Operation/Storage/Transport: 5g, 150 Hz, Criterion 3
Type of test	Free fall in acc. with IEC 60068-2-32
Test result	1 m
Noise emission	EN 61000-6-3 +A11
Noise immunity	EN 61000-6-2:2005
Vibration (storage/transport)	5g, 10 Hz ... 150 Hz, in accordance with IEC 60068-2-6
Vibration (operation)	in accordance with IEC 60068-2-6: 5g, 10 Hz ... 150 Hz

## Classifications

### eCl@ss

eCl@ss 4.0	27250501
eCl@ss 4.1	27250501
eCl@ss 5.0	27250501
eCl@ss 5.1	27250501
eCl@ss 6.0	19170106
eCl@ss 7.0	19170106
eCl@ss 8.0	19170106

### ETIM

ETIM 3.0	EC000734
ETIM 4.0	EC001478
ETIM 5.0	EC000734

### UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201410
UNSPSC 13.2	43201410

## Approvals

### Approvals

#### Approvals

UL Listed / cUL Listed / EAC / EAC / cULus Listed

## Industrial Ethernet Switch - FL NAT SMN 8TX - 2989365

### Approvals

Ex Approvals

---

Approvals submitted

---

### Approval details

UL Listed 

cUL Listed 

EAC

EAC

cULus Listed 

---

Phoenix Contact 2016 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
Smart Managed Narrow NAT switch with eight 10/100 Mbps RJ45 ports and 1:1 NAT router function	2989365	FL NAT SMN 8TX	<a href="#">Buy on EAN</a>