



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. [HERE](#)

Fuse modular terminal block - PT 10,3-HESILED 1000V - 3062143

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Fuse modular terminal block, Connection method: Push-in connection, Cross section: 1.5 mm²- 10 mm², AWG: 16 - 6, Nominal current: 20 A, Nominal voltage: 1000 V, Width: 17.6 mm, Fuse type: Midget / 10.3 x 38, Mounting type: NS 35/7,5, NS 35/15, Color: black

The illustration shows the version without LED/light indicator

Why buy this product

- The Push-in connection terminal blocks are characterized by the system features of the CLIPLINE complete system and by easy and tool-free wiring of conductors with ferrules or solid conductors
- The compact design and front connection enable wiring in a confined space
- In addition to the testing facility in the double function shaft, all terminal blocks provide an additional test connection
- Dielectric strength up to 1000 V DC

Key Commercial Data

Packing unit	10 STK
Minimum order quantity	10 STK
GTIN	 4 046356 724739

Technical data

General

Number of levels	1
Number of connections	2
Nominal cross section	10 mm ²
Color	black
Insulating material	PA
Flammability rating according to UL 94	V0
Fuse	Midget / 10.3 x 38
Rated surge voltage	6 kV
Degree of pollution	3
Overvoltage category	III
Insulating material group	IIIa
Maximum power dissipation	3 W (Fuse insert)
LED voltage range	250 V AC ... 1000 V AC
Connection in acc. with standard	IEC 60269-1/-2

Fuse modular terminal block - PT 10,3-HESILED 1000V - 3062143

Technical data

General

Maximum load current	20 A (the current is determined by the fuse used)
Nominal current I_N	20 A (the current is determined by the fuse used)
Nominal voltage U_N	1000 V (the voltage is determined by the fuse used)
Open side panel	No

Dimensions

Width	17.6 mm
Length	87 mm
Height NS 35/7,5	63 mm
Height NS 35/15	70.5 mm

Connection data

Conductor cross section solid min.	1.5 mm ²
Conductor cross section solid max.	10 mm ²
Conductor cross section flexible min.	1.5 mm ²
Conductor cross section flexible max.	10 mm ²
Conductor cross section AWG min.	16
Conductor cross section AWG max.	6
Conductor cross section flexible, with ferrule without plastic sleeve min.	1.5 mm ²
Conductor cross section flexible, with ferrule without plastic sleeve max.	10 mm ²
Conductor cross section flexible, with ferrule with plastic sleeve min.	1.5 mm ²
Conductor cross section flexible, with ferrule with plastic sleeve max.	10 mm ²
Connection method	Push-in connection
Stripping length	18 mm

Standards and Regulations

Connection in acc. with standard	IEC 60269-1/-2
Flammability rating according to UL 94	V0

Classifications

eCl@ss

eCl@ss 4.0	27141118
eCl@ss 4.1	27141118
eCl@ss 5.0	27141118
eCl@ss 5.1	27141116
eCl@ss 6.0	27141116
eCl@ss 7.0	27141116
eCl@ss 8.0	27141116

ETIM

ETIM 3.0	EC000899
----------	----------

Fuse modular terminal block - PT 10,3-HESILED 1000V - 3062143

Classifications

ETIM


ETIM 4.0	EC000899
ETIM 5.0	EC000899

UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39121410

Drawings

Circuit diagram



Phoenix Contact 2016 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
Fuse modular terminal block, Connection method: Push-in connection, Cross section: 1.5 mm ² - 10 mm ² , AWG: 16 - 6, Nominal current: 20 A, Nominal voltage: 1000 V, Width: 17.6 mm, Fuse type: Midget / 10.3 x 38, Mounting type: NS 35/7,5, NS 35/15, Color: black	3062143	PT 10,3-HESILED 1000V	Buy on EAN