



At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. HERE



Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Test plug, with twist grip, VDE coded A7, Width: 71 mm, Color: gray



Why buy this product

- Easy and time saving, thanks to functional grouping of switching operations
- Cost-effective, thanks to the tailored, modular design and use of standardized CLIPLINE complete accessories
- Space saving, thanks to offset test socket arrangement
- Safe, thanks to guided operation with patented twist grip
- The integrated, robust switch contact is designed for the most stringent demands, and the use of high-quality materials ensures the transmission of signal currents, even after multiple actuations
- The automatically generated transformer short circuit and the shock-proof design ensure the highest degree of safety during measurement
- Maximum safety with leading and automatic transformer short circuit

Key Commercial Data

Packing unit	1 STK
GTIN	4 046356 943703

Technical data

General

Note	A detailed circuit diagram can be found under Miscellaneous Downloads			
Number of levels	1			
Nominal cross section	6 mm²			
Color	gray			
Insulating material	PA			
Flammability rating according to UL 94	V0			
Rated surge voltage	5 kV			
Overvoltage category	III			
Insulating material group	I			
Maximum load current	24 A			
Nominal current I _N	24 A			
Nominal voltage U _N	400 V AC/DC			
Open side panel	No			



Technical data

General

Number of positions	7
Dimensions	

Dimensions

Width	71 mm
Length	86 mm

Connection data

Note	The conductor cross section depends on the cable lug used		
Conductor cross section flexible min.	0.5 mm ²		
Conductor cross section flexible max.	2.5 mm²		
Min. AWG conductor cross section, flexible	20		
Max. AWG conductor cross section, flexible	14		

Assembly

Mounting type	Insertion in base strip	
Min. tightening torque of the test socket screw:	0.5 Nm	
Max. tightening torque of the test socket screw:	0.6 Nm	

Standards and Regulations

Flammability rating according to UL 94	V0

Classifications

eCl@ss

eCl@ss 5.1	27141120
eCl@ss 6.0	27141141
eCI@ss 8.0	27440313

ETIM

ETIM 4.0	EC000897
ETIM 5.0	EC002255

Approvals

Approvals

Approvals

UL Recognized / cUL Recognized / cULus Recognized

Ex Approvals



Approvals

Approvals submitted

Approval details


UL Recognized \$\)	
	D
Nominal current IN	10 A
Nominal voltage UN	300 V

cUL Recognized 53		
	D	
Nominal current IN	10 A	
Nominal voltage UN	300 V	

Drawings




Circuit diagram



Circuit diagram shows the test terminal strip with test plug inserted



Dimensional drawing



Phoenix Contact 2016 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com





Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, <u>click on the green button</u>.

Product	Code	Reference	Product link
Test plug, with twist grip, VDE coded A7, Width: 71 mm, Color: gray	3069484	FTPR-2/A7	Buy on EAN