



At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking <u>HERE</u>

Heavy-duty plug-in connectors

## Accessories Crimping tools



Crimp contacts must be connected to the conductors. This is done by means of crimping. Crimping pliers are available for copper litz wires, coaxial contacts, and fiber optic contacts. The crimping pliers have locators that facilitate accurate positioning of the crimp contact and conductor. To ensure a reliable crimp connection, the pliers must be closed correctly. This is guaranteed by means of a pressure lock.

The requirements placed on crimp connections are described in EN 60352-2. A major feature of the quality of the crimp connection is the tensile strength of the connection. It is simple to measure.



Crimping tools/stripping pliers

Ordering data

|  | Ordering data  |                               |                |
|--|--|-------------------------------|----------------|
| Description  | Туре   | Order No.                     | Pcs. /<br>Pkt. |
| Crimping pliers, for turned contacts with 1.6 / 2.5 / 4.0 mm pin diameters, each with locator  |  |                               |                |
| - For CK1,6-ED , CK2,5-ED, CK4.0-E D 0.5-4 mm <sup>2</sup> turned contacts   | CRIMPFOX-TC 4  | 1212113                       | 1              |
| - For CK4,0-ED 6 - 10 mm² turned contacts  | CRIMPFOX-TC 10   | 1212114                       | 1              |
| <ul> <li>For VSCD turned contacts (D-SUB contacts);</li> <li>crimping tool with four mandrels</li> </ul>                                 | CRIMPFOX RC 2,5  | 1205448                       | 1              |
| - For CK1,6-ED CK2,5-ED; 0.14 - 4 mm² turned contacts  | CRIMPFOX-1,6/2,5-ED-4,0  | 1687419                       | 1              |
| Coaxial plug-in connector, 1.69 mm, 3.25 mm, 4.52 mm, three marked die stations, pressure lock can be released, lateral entry, hex crimp | CRIMPFOX-CX 4,52   | 1212094                       | 1              |
| Crimping pilers - For CK1,6-ER rolled contacts - For CK1,6-EDPOF turned fiber optic contacts   | CRIMPFOX-1,6-ER-1,50-AT<br>CRIMPFOX-1,6-ED-POF-N                       | 1884843<br>1584839            | 1              |
| Replacement die  |  |                               |                |
| - For CRIMPFOX 1,6/2,5-ED-4,0<br>- For CRIMPFOX-TC 4<br>- For CRIMPFOX-TC 10   | CRIMPFOX-1,6/2,5-ED-4,0 DIE<br>CRIMPFOX-TC 4/DIE<br>CRIMPFOX-TC 10/DIE | 1886948<br>1212295<br>1212296 | 1 1            |
| Stripping tool for FO cables   |  |                               |                |
| Stripping pliers for individual elements     Crimping machine, with quantity counter and foot switch                                     | PSM-FO-STRIP   | 2744199                       | 1              |
|  |  |                               |                |
| 230 V version<br>120 V version   | CF 500-230V<br>CF 500-120V   | 1208348<br>1208351            | 1              |
| Die for turned contacts with pin diameters of 2.5 and 4.0 mm (CK 2,5,CK 4,0) 0.14 - 4 mm <sup>2</sup>                                    | CF 500/DIE TC 4  | 1212237                       | 1              |
| Die for (CK 4,0) 6 - 10 mm² turned contacts  | CF 500/DIE TC 10   | 1212260                       | 1              |
| Cover for insulated cable lugs (RCI, TC4)  | CF 500/COV RCI   | 1212255                       | 1              |
| Cover for unassigned dies for self-assembly, TC 10, among others   | CF 500/COV   | 1212250                       | 1              |
| For TWIN ferrules (AI-TWIN)  | CF 500/COV AI TWIN   | 1212266                       | 1              |
| Basic pliers, for accommodating dies for various contact types, pressure lock can be unlocked, lateral entry                             |  |                               |                |
|  | CRIMPFOX-M   | 1212072                       | 1              |
| Dies, for CRIMPFOX-M   |  |                               |                |
| For turned contacts with pin diameters of 2.5 mm and 4.0 mm (CK 2,5,CK 4,0), cross section: 0.14 - 4 mm <sup>2</sup>                     | CRIMPFOX-M TC 4/DIE  | 1212075                       | 1              |
| For turned contacts with pin diameter of 4 mm (CK 4,0), cross section: 6 - 10 mm <sup>2</sup>  | CRIMPFOX-M TC 10/DIE   | 1212076                       | 1              |

## Accessories Assembly/removal tools



It is sometimes necessary to use assembly tools in cases of small conductor cross sections. They are used to press the crimp contact firmly into the contact insert.

If incorrect components are installed or alterations are made to the wiring, it will be necessary to remove a contact that is already engaged. This is done with the aid of a removal tool.



|   | Ordering data    |           |                |
|---|------------------|-----------|----------------|
| Description   | Туре             | Order No. | Pcs. /<br>Pkt. |
| Assembly tool - For CK1,6-ED/CK2,5-ED/CK1,6-ER contacts | CK1,6/2,5-MWZ    | 1676734   | 1              |
| Removal tool - For CK1,6-ED/CK1,6-ER/CK1,6POF contacts  | VC-EW 1,6        | 1884869   | 1              |
| - For CK2,5-ED contacts                                 | CK2,5-EWZ        | 1662722   | 1              |
| - For CK4,0-ED contacts                                 | CK4,0-EWZ        | 1662735   | 1              |
| - For VSCD D-SUB contacts                               | EWR              | 1665075   | 1              |
| - For HC-M-04KOAX coaxial contacts                      | HC-M4-KOAX-EWZ   | 1676747   | 1              |
| - For HC-M-EMV EMC plug-in connectors                   | HC-M-EMV-KON-EWZ | 1678635   | 1              |
| - For locking sleeve of the HC-M-HV-MOD module          | HC-M-AH-EWZ      | 1584826   | 1              |

PHOENIX CONTACT | 563 562 PHOENIX CONTACT For additional information, visit www.phoenixcontact.net/products





Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, <u>click on the green button</u>.

| Product   | Code Reference |                   | Product link |
|---|----------------|-------------------|--------------|
| Crimping pliers, for turned contacts, 0.5 - 4.0 mm <sup>2</sup> , square crimp, incl. contact support | 1212113        | CRIMPFOX-TC<br>4  | Buy on EAN   |
| Crimping pliers, for turned contacts, 6.0 - 10 mm <sup>2</sup> , square crimp, incl. contact locator  | 1212114        | CRIMPFOX-TC<br>10 | Buy on EAN   |