

Reference: 3RA1316-8XB34-1DM4

CONTACTOR COMBINATION FOR REV. 3-PH, 4KW/400V, 3-POLE, SIZE S SCREW CONNECTION 220 V DC WITH 2X FRONT AUX. CONTACTS ELECTR. AND MECH. LOCKING WITH 2X VARISTOR MOUNTED

Buy it at [Electric Automation Network](#)



General technical data:	
Product function	reversing contactor
Size of contactor	S00
Witd>	mm 90
Height	mm 67
Depth	mm 72
Equipment marking acc. to DIN EN 61346-2	Q
Equipment marking acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750	K
Control circuit/ Control:	
Type of voltage of the control supply voltage	DC
Control supply voltage 1	
at DC	
— rated value	V 220
Main circuit:	
Operating current at AC-3 at 400 V rated value	A 9
Operating power at AC-3 at 400 V rated value	kW 4
Auxiliary circuit:	
Number of NC contacts for auxiliary contacts per direction of rotation	2
Number of NO contacts for auxiliary contacts per direction of rotation	2

Connections/ Terminals:			
Type of electrical connection for main current circuit	screw-type terminals		
Mounting type	screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 50022		
Ambient conditions:			
Ambient temperature during operation	°C	-25 ... +60	
Protection class IP on the front	IP20		
Certificates/ approvals:			
General Product Approval	Declaration of Conformity	Test Certificates	Shipping Approval
		spezielle Prüfbescheinigungen	
Shipping Approval			other
			Umweltbestätigung
other			
Bestätigungen			