

Reference: 3RA1316-8XB37-1DE4

CONTACTOR COMBIN. TO REVERS., AC-3,
4KW/400V, 3-POLE SIZE S00 SCREW
CONNECTION, 3NO+1NC2X, 60 V DC
ELECTR. AND MECH. LOCKED VARISTOR

Buy it at [Electric Automation Network](#)



| | |
|---|---------------------|
| General technical data: | |
| Product function | reversing contactor |
| Size of contactor | S00 |
| Witd> | mm 90 |
| Height | mm 67 |
| Depth | mm 72 |
| Equipment marking acc. to DIN EN 61346-2 | Q |
| Equipment marking acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750 | K |
| Control circuit/ Control: | |
| Type of voltage of the control supply voltage | DC |
| Control supply voltage 1 | |
| at DC | |
| — rated value | V 60 |
| Main circuit: | |
| Operating current at AC-3 at 400 V rated value | A 9 |
| Operating power at AC-3 at 400 V rated value | kW 4 |
| Auxiliary circuit: | |
| Number of NC contacts for auxiliary contacts per direction of rotation | 1 |
| Number of NO contacts for auxiliary contacts per direction of rotation | 3 |

| | | | |
|--|--|-------------------------------|-------------------|
| Connections/ Terminals: | | | |
| Type of electrical connection for main current circuit | screw-type terminals | | |
| Mounting type | screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 50022 | | |
| Ambient conditions: | | | |
| Ambient temperature during operation | °C | -25 ... +60 | |
| Protection class IP on the front | IP20 | | |
| Certificates/ approvals: | | | |
| General Product Approval | Declaration of Conformity | Test Certificates | Shipping Approval |
| | | spezielle Prüfbescheinigungen | |
| Shipping Approval | | | other |
| | | | Umweltbestätigung |
| other | | | |
| Bestätigungen | | | |