

Reference: 3RA1326-8XB30-1AG2

REVERSING CONTACTOR COMBINATION  
AC-3 11KW/400V, SIZE S0 110V,  
50/60HZ

Buy it at [Electric Automation Network](#)



General technical data:	
Product function	reversing contactor
Size of contactor	S0
Width	mm 100
Height	mm 86
Depth	mm 91
Equipment marking acc. to DIN EN 61346-2	Q
Equipment marking acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750	K
Control circuit/ Control:	
Type of voltage of the control supply voltage	AC
Control supply voltage 1	
at AC	
— at 50 Hz rated value	V 110
— at 60 Hz rated value	V 110
Control supply voltage frequency	
1 rated value	Hz 50
2 rated value	Hz 60
Main circuit:	
Operating current at AC-3 at 400 V rated value	A 25
Operating power at AC-3 at 400 V rated value	kW 11

Auxiliary circuit:	
Number of NC contacts for auxiliary contacts per direction of rotation	0
Number of NO contacts for auxiliary contacts per direction of rotation	0
Connections/ Terminals:	
Type of electrical connection for main current circuit	screw-type terminals
Mounting type	screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 50022
Ambient conditions:	
Ambient temperature during operation	°C -25 ... +60
Protection class IP on the front	IP20
Certificates/ approvals:	
General Product Approval	Declaration of Conformity
Shipping Approval	Shipping Approval
	other
	Umweltbestätigung
other	
sonstig	Bestätigungen