

Reference: 3RA1334-8XB36-1BB4

CONTACTOR COMBIN. TO REVERS. 15  
KW, SIZE S2, 24 V DC, WITH AUX.  
SWITCH 2 X 1NO + 1NC

Buy it at [Electric Automation Network](#)



General technical data:	
Product function	reversing contactor
Size of contactor	S2
Width	mm 120
Height	mm 133
Depth	mm 130
Equipment marking acc. to DIN EN 61346-2	Q
Equipment marking acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750	K
Control circuit/ Control:	
Type of voltage of the control supply voltage	DC
Control supply voltage 1	
at DC	
— rated value	V 24
Main circuit:	
Operating current at AC-3 at 400 V rated value	A 32
Operating power at AC-3 at 400 V rated value	kW 15
Auxiliary circuit:	
Number of NC contacts for auxiliary contacts per direction of rotation	1
Number of NO contacts for auxiliary contacts per direction of rotation	1

Connections/ Terminals:	
Type of electrical connection for main current circuit	screw-type terminals
Mounting type	screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 50022
Ambient conditions:	
Ambient temperature during operation	°C -25 ... +60
Protection class IP on the front	IP20
Certificates/ approvals:	
General Product Approval	Declaration of Conformity
	Shipping Approval
Shipping Approval	other
	Umweltbestätigung Bestätigungen