

Reference: 3RU1136-4FD0

OVERLOAD RELAY, 28...40 A, 1NO+1NC,
SIZE S2, CLASS 10, FOR CONTACTOR
MOUNTING, AUXILIARY SWITCH: CAGE
CLAMP

Buy it at Electric Automation Network



product brand name	SIRIUS
Product designation	thermal overload relay
General technical data:	
Size of overload relay	S2
Size of contactor can be combined company-specific	S2
Power loss [W] total typical	9 W
Insulation voltage with degree of pollution 3 rated value	690 V
Surge voltage resistance rated value	6 kV
Protection class IP	
on the front	IP20
Shock resistance	8g / 10 ms
Type of protection	DMT 98 ATEX G 001
Protection against electrical shock	finger-safe
Equipment marking acc. to DIN EN 81346-2	F
Ambient conditions:	
Installation altitude at height above sea level maximum	2 000 m
Ambient temperature	
during operation	-20 ... +70 °C
during storage	-55 ... +80 °C
during transport	-55 ... +80 °C
Relative humidity during operation	100 %

Main circuit:	
Number of poles for main current circuit	3
Adjustable pick-up value current of the current-dependent overload release	28 ... 40 A
Operating voltage	
at AC-3 rated value maximum	690 V
Auxiliary circuit:	
Number of NC contacts	
for auxiliary contacts	1
Number of NO contacts	
for auxiliary contacts	1
Number of CO contacts	
for auxiliary contacts	0
Operating current of auxiliary contacts at AC-15	
at 24 V	3 A
at 110 V	3 A
at 120 V	3 A
at 125 V	3 A
at 230 V	2 A
at 400 V	1 A
Operating current of auxiliary contacts at DC-13	
at 24 V	1 A
at 110 V	0.22 A
at 125 V	0.22 A
at 220 V	0.11 A
Protective and monitoring functions:	
Trip class	CLASS 10
Short-circuit protection	
Design of the fuse link	
for short-circuit protection of the auxiliary switch required	fuse gL/gG: 6 A, quick: 10 A
Installation/ mounting/ dimensions:	
Mounting position	with vertical mounting surface +/-135° rotatable, with vertical mounting surface +/- 45° tiltable to the front and back
Mounting type	direct mounting
Height	105 mm
Width	55 mm
Depth	118 mm
Required spacing	

with side-by-side mounting	
— forwards	0 mm
— Backwards	0 mm
— upwards	0 mm
— downwards	0 mm
— at the side	0 mm
for grounded parts	
— forwards	0 mm
— Backwards	0 mm
— upwards	0 mm
— at the side	6 mm
— downwards	0 mm
for live parts	
— forwards	0 mm
— Backwards	0 mm
— upwards	0 mm
— downwards	0 mm
— at the side	6 mm
Connections/Terminals:	
Product function	
removable terminal for auxiliary and control circuit	No
Type of electrical connection	
for main current circuit	screw-type terminals
for auxiliary and control current circuit	Cage Clamp terminals
Type of connectable conductor cross-sections	
for main contacts	
— solid	2x (0.75 ... 16 mm ²)
— stranded	2x (0.75 ... 25 mm ²), 0.75 ... 35 mm ²
— finely stranded with core end processing	2x (0.75 ... 16 mm ²), 0.75 ... 25 mm ²
at AWG conductors for main contacts	2x (18 ... 3), 1x (18 ... 1)
Type of connectable conductor cross-sections	
for auxiliary contacts	
— solid	2x (0.5 ... 2.5 mm ²)
— finely stranded with core end processing	2x (0.5 ... 1.5 mm ²)
— finely stranded without core end processing	2x (0.5 ... 1.5 mm ²)
at AWG conductors for auxiliary contacts	2x (20 ... 14)