

Reference: 3SB1208-7JW01

COORDINATE SWITCH, 22MM, ROUND, PLASTIC, BLACK, PLASTIC FRONT RING BLACK, 4 SWITCH POSITIONS, MOMENTARY CONTACT, WITH MECHANICAL INTERLOCK IN O POSITION, WITH HOLDER, 1NO PER DIRECTION

Buy it at [Electric Automation Network](#)



Enclosure:	
Shape of the enclosure front	round
Material of the enclosure	plastic
Actuator:	
Design of the operating mechanism	joystick
Number of switching positions	4
Button:	
Design of the button	raised
Color of the button	black
Front ring:	
Product component front ring	Yes
Material of the front ring	plastic
Color of the front ring	black
General technical data:	
Type of voltage	
of the operating voltage	AC/DC
Protection class IP	IP65
Vibration resistance	
acc. to IEC 60068-2-6	20 ... 200 Hz: 5g
Operating frequency maximum	1 000 1/h
Mechanical service life (switching cycles)	

typical	500 000
Equipment marking	
acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750	S
acc. to DIN EN 61346-2	S
acc. to DIN EN 81346-2	S
Operating voltage	
rated value	5 ... 500 V
Auxiliary circuit:	
Number of NC contacts	
for auxiliary contacts	0
Number of NO contacts	
for auxiliary contacts	4
Number of CO contacts	
for auxiliary contacts	0
Connections/ Terminals:	
Type of electrical connection	screw-type terminals
Tightening torque of the screws in the bracket	0.8 N·m
Ambient conditions:	
Ambient temperature	
during operation	-25 ... +70 °C
during storage	-40 ... +80 °C
Installation/ mounting/ dimensions:	
Mounting type	front mounting
Height	45 mm
Witd>	45 mm
Depth	142 mm
Shape of the installation opening	round
Mounting diameter	22 mm
Mounting height	82 mm
Installation witd>	30 mm