

Reference: 3TH2040-1BW4

CONTACTOR RELAY 40E EN 50 011 4NO, TAB CONNECTOR DC OPERATION DC SOLENOID SYSTEM DC 48V

Buy it at [Electric Automation Network](#)

General technical data:	
Size of contactor	0
Ambient temperature during operation	-25 ... +55 °C
Protection class IP on the front	IP20
Equipment marking acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750	K
Equipment marking acc. to DIN EN 61346-2	K
Equipment marking acc. to DIN EN 81346-2	K
Control circuit/ Control:	
Type of voltage of the control supply voltage	DC
Control supply voltage	
at DC	
— rated value	48 V
Auxiliary circuit:	
Operating current at AC-15	
at 230 V rated value	4 A
at 400 V rated value	3 A
Identification number and letter for switching elements	40 E
Number of NC contacts for auxiliary contacts	0
lagging switching	0
delayed switching	0
make-before-break switching	0
Number of NO contacts for auxiliary contacts	4
delayed switching	0
leading contact	0
make-before-break switching	0
Number of CO contacts for auxiliary contacts	0
Connections/ Terminals:	

Type of electrical connection for auxiliary and control current circuit	tab terminals 2x 2.8 mm
Mechanical data:	
Mounting type	screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 50022
Width	45 mm
Height	48 mm
Depth	64.5 mm