

Reference: 3TH2262-1AP0

CONTACTOR RELAY 62E EN 50 011 6NO+2NC, TAB CONNECTOR WIDTH 45MM AC
OPERATION AC 230/220V 50HZ, 276/264V 60HZ

Buy it at Electric Automation Network

General technical data:	
Size of contactor	0
Ambient temperature during operation	-25 ... +55 °C
Protection class IP on the front	IP20
Equipment marking acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750	K
Equipment marking acc. to DIN EN 61346-2	K
Equipment marking acc. to DIN EN 81346-2	K
Control circuit/ Control:	
Type of voltage of the control supply voltage	AC
Control supply voltage frequency	
1 rated value	50 Hz
2 rated value	60 Hz
Control supply voltage	
at AC	
— at 50 Hz	
— rated value	230 V
— at 60 Hz	
— rated value	277 V
Auxiliary circuit:	
Operating current at AC-15	
at 230 V rated value	4 A
at 400 V rated value	3 A
Identification number and letter for switching elements	62 E
Number of NC contacts for auxiliary contacts	2
lagging switching	0
delayed switching	0
make-before-break switching	0

Number of NO contacts for auxiliary contacts	6
delayed switching	0
leading contact	0
make-before-break switching	0
Number of CO contacts for auxiliary contacts	0
Connections/ Terminals:	
Type of electrical connection for auxiliary and control current circuit	tab terminals 2x 2.8 mm
Mechanical data:	
Mounting type	screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 50022
Width	45 mm
Height	48 mm
Depth	96 mm