

Reference: 3TX4010-4A

AUXILIARY CONTACT BLOCK WITHOUT POSITION INDICATION FOR PLUGGING ONTO CONTACTORS 1NO WITH DELAYED CONTACTS

Buy it at [Electric Automation Network](#)



General technical data:		
product brand name	SIRIUS	
Suitability for use	Contactor relay and power contactor	
Protection class IP on the front	IP20	
Ambient temperature		
during storage	°C	-55 ... +80
during operation	°C	-25 ... +55
Mechanical service life (switching cycles) typical	10 000 000	
Insulation voltage with degree of pollution 3 rated value	V	690
Surge voltage resistance rated value	kV	6
Auxiliary circuit:		
Number of NC contacts for auxiliary contacts		
instantaneous contact	0	
lagging switching	0	
Number of NO contacts for auxiliary contacts		
instantaneous contact	0	
leading contact	1	
Operating current of auxiliary contacts at AC-12		
at 24 V	A	10
at 230 V	A	10
maximum	A	10

Operating current		
of auxiliary contacts		
— at AC-14		
— at 125 V	A	10
— at AC-15		
— at 24 V	A	10
— at 230 V	A	5.6
— at 400 V	A	3.6
at AC-15 at 690 V rated value	A	2.3
Operating current		
of auxiliary contacts at DC-13		
— at 24 V	A	10
— at 60 V	A	5
— at 110 V	A	1.14
— at 220 V	A	0.48
Installation/ mounting/ dimensions:		
Mounting type		snap-on mounting
Witd>	mm	12
Height	mm	70
Depth	mm	51.5
Connections/ Terminals:		
Type of connectable conductor cross-sections		
for auxiliary contacts		
— finely stranded		
— with core end processing		2x (0.5 ... 1.0 mm ²), 2x (0.75 ... 2.5 mm ²)
at AWG conductors for auxiliary contacts		2x (18 ... 12)
Safety related data:		
Product function positively driven operation acc. to IEC 60947-5-1		Yes
Certificates/ approvals:		
General Product Approval	Test Certificates	Shipping Approval
	Werksbescheinigungen	sonstig
Shipping Approval	other	
	Bestätigungen	