

Reference: 6SL3211-2AB17-5UA1

SINAMICS G110 - CPM110 AC-DRIVE, WITHOUT FILTER 1AC200-240V +10/-10% 47-63HZ ANALOG INPUT CT: 0.75KW; VT: 0.75KW CT-OVERLOAD: 150% 60S 150 X 90 X 131 (HXWxD) PROTECTION IP20 AMBIENT TEMP -10 TO +40 DEG C WITHOUT BOP WITHOUT RS485-INTERFACE VISCOUNT DEFAULT DATA

Buy it at [Electric Automation Network](#)

Product	
Article Number (Market Facing Number)	6SL3211-2AB17-5UA1
Product Description	SINAMICS G110 - CPM110 AC-DRIVE, WITHOUT FILTER 1AC200-240V +10/-10% 47-63HZ ANALOG INPUT CT: 0.75KW; VT: 0.75KW CT-OVERLOAD: 150% 60S 150 X 90 X 131 (HXWxD) PROTECTION IP20 AMBIENT TEMP -10 TO +40 DEG C WITHOUT BOP WITHOUT RS485-INTERFACE VISCOUNT DEFAULT DATA
Product family	Not available
Product Lifecycle (PLM)	PM300:Active Product
Price data	
Price Group / Headquarter Price Group	325 / 334
List Price	Show prices
Customer Price	Show prices
Metal Factor	None
Delivery information	
Export Control Regulations	ECCN : N / AL : N
Standard lead time ex-works	28 Day/Days
Net Weight (kg)	0,800 Kg
Product Dimensions (W x L x H)	Not available
Packaging Dimension	100,00 x 180,00 x 160,00
Package size unit of measure	MM
Quantity Unit	1 Piece
Packaging Quantity	1
Atd>	
EAN	4042948660409
UPC	Not available
Commodity Code	85044084

LKZ_FDB/ CatalogID	D11.1SD
Product Group	9760
Country of origin	Great Britain
Compliance with the substance restrictions according to RoHS directive	Since: 01/07/06
Product class	A: Standard product which is a stock item could be returned within the returns guidelines/period.
Obligation Category for taking back electrical and electronic equipment after use	No obligation to take back electrical and electronic equipment after use
Classifications	
	Not available