



**Electric Automation**  
Automation specialists

Référence: VE5-1

Code: 1SBN030110R1000

VE5-1 Bloc Contacteur Accessoires

Achat de Electric Automation Network



VE5-1 Block Contactor Accessories

## Ordering

EAN:	3471522121370
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85389099

## Dimensions

Product Net Weight:	0.076 kg
---------------------	----------

## Container Information

Package Level 1 Units:	1 piece
Package Level 1 Gross Weight:	0.076 kg
Package Level 1 EAN:	3471522121370
Package Level 2 Units:	90 piece

## Environmental

RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
--------------	---

## Additional Information

Conventional Free-air Thermal Current ( $I_{th}$ ):	acc. to IEC 60947-5-1, $q = 40\text{ °C}$ 16.0 A
IIT Publishing Status:	Level 0 - Information enabled

Mechanical Durability:	5 million
Mounted Auxiliary Contacts:	0 NO, 2 NC
Mounting on Contactors:	A 9 ...A 40, N
Mounting Type:	rail or plate not supplied
Number of Auxiliary Contacts NC:	2
Power Loss:	at Rated Operating Conditions per Pole 0.1 W
Product Main Type:	Accessories for Block Contactors
Product Name:	Block Contactor Accessories
Rated Breaking Capacity acc. to IEC 60947-5-1:	10 x I <sub>e</sub> AC-15
Rated Frequency (f):	Supply Circuit 50 Hz Supply Circuit 60 Hz
Rated Insulation Voltage (U <sub>i</sub> ):	acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V acc. to UL/CSA 600 V
Rated Making Capacity acc. to IEC 60947-5-1:	10 x I <sub>e</sub> AC-15
Rated Operational Current AC-15 (I <sub>e</sub> ):	(220 / 240 V) 4 A (24 / 127 V) 6 A (380 / 440 V) 3 A (500 V) 2 A (690 V) 2 A
Rated Operational Current DC-13 (I <sub>e</sub> ):	(125 V) 0.55 A (24 V) 6 A (250 V) 0.3 A (48 V) 2.8 A (72 V) 1 A
Rated Operational Voltage:	Auxiliary Circuit 690 V
Rated Short-time Withstand Current (I <sub>cw</sub> ):	for 0.1 s 140.0 A for 1 s 100 A
Terminal Type:	Screw Terminals
Version:	Mechanical/Electrical

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SBC100122C0202_Ch04
Declaration of Conformity - CE:	1SBD250802C3000
GOST Certificate:	GOST_POCCFRME77B07175
RINA Certificate:	RINA_ELE128713XG001
RoHS Information:	1SBC101061D0201

## Classifications

E-nummer:	3228825
ETIM 4:	EC002498 - Accessories for low-voltage switch technology
ETIM 5:	EC002498 - Accessories for low-voltage switch technology

UNSPSC:

39120000