



**Electric Automation**  
Automation specialists

Référence: LS31P41L20  
Code: 1SBV010141R1320

Limit LS31P41L20 Commutateur

Achat de Electric Automation Network



## LS31P41L20 Limit Switch

### Ordering

EAN:	3471522000873
Minimum Order Quantity:	10 piece
Customs Tariff Number:	85369085

### Dimensions

Product Net Width:	30 mm
Product Net Weight:	0.090 kg

### Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	118 mm
Package Level 1 Height:	54 mm
Package Level 1 Length:	32 mm
Package Level 1 Gross Weight:	0.09 kg
Package Level 1 EAN:	3471522000873

### Environmental

Ambient Air Temperature:	Operation -25 ... +70 °C Storage -30 ... +80 °C
--------------------------	--

Resistance to Shock acc. to IEC 60068-2-27:	Half-sine Pulse for 11 ms, No Change in Contact Position 50 m/s <sup>2</sup>
Resistance to Vibrations acc. to IEC 60068-2-6:	25g (10 to 500 Hz) no change in position of contacts greater than 100 µs

## Technical UL/CSA

Pilot Duty of Contact Elements acc. UL508:	A600 Q600
Flammability According to UL94:	V0

## Additional Information

Action Type of the Contact Element (acc. to IEC 60947-5-1):	simultaneous slow action contacts
Actuation Speed:	acc. to IEC 60947-5-1 Max. 1.50 m/s acc. to IEC 60947-5-1 Min. 0.06 m/s
Actuation Torque:	acc. to IEC 60947-5-1 Min. 0.10 N·m
Actuator Type:	Ø 18 mm polyamide roller lever
Angular Head Adjustment:	adjustable head every 90°
Angular Lever Adjustment:	10° in 10°
Climatic Withstand:	according to IEC 68-2-3 and salty mist according to IEC 68-2-11
Connecting Capacity:	AWG 20 ... AWG 14 0.5 ... 2.5 mm <sup>2</sup>
Connecting terminals (delivered in open position):	M3.5 (+,-) pozidriv 2 screw with cable clamp
Consistency (Measured over 1 Million Operations):	0.1 mm
Contact Element Form (acc. to IEC 60947-5-1):	Zb
Conventional Free-air Thermal Current (I <sub>th</sub> ):	acc. to IEC 60947-5-1, q = 40 °C 10.0 A
Degree of Protection:	acc. to IEC 60529 IP65
Electrical Shock Protection acc. to IEC 536:	Double insulation - Class II
IIT Publishing Status:	Level 0 - Information enabled
Load Factor:	.5
Maximum Electrical Switching Frequency:	3600 cycles per hour
Mechanical Durability:	10 million
Mounting by Screws (not supplied):	2 x M4 screws
Mounting Position:	all positions are authorised
Movement to be Detected:	30° Cam Translation Movement
Number and Type of Bottom Cable Glands:	Pg 11 Cable Gland
Number of Auxiliary Contacts NO:	2
Operating Head Shape:	A shape acc. EN 50047
Positive Opening Operation of NC Contact(s):	No

Positive Opening Operation Torque (Direct Opening Action):	Minimum Torque acc. to IEC 60947-5-1 0.32 N·m
Product Main Type:	LS30
Product Name:	Limit Switch
Rated Frequency (f):	Supply Circuit 50 Hz Supply Circuit 60 Hz
Rated Impulse Withstand Voltage (U <sub>imp</sub> ):	6 kV
Rated Insulation Voltage (U <sub>i</sub> ):	acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V acc. to UL/CSA 600 V
Rated Operational Current AC-15 (I <sub>e</sub> ):	(130 V) 5.5 A (230 V) 3.1 A (240 V) 3 A (24 V) 10 A (400 V) 1.8 A
Rated Operational Current DC-13 (I <sub>e</sub> ):	(110 V) 0.6 / 66 A (24 V) 2.8 / 67.2 A (250 V) 0.27 / 67.5 A
Resistance Between Contacts:	25 mΩ
Standards:	IEC 60947-1, IEC 60947-5-1, EN 60947-1, EN 60947-5-1, UL 508 and CSA C22-2 N°14
Terminal Marking:	according to EN 50013

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SBC001699R1002
Declaration of Conformity - CE:	1SBD250881C2000

## Classifications

ETIM 4:	EC001829 - Position switch modular
ETIM 5:	EC001829 - Position switch modular
UNSPSC:	39121500