

eliwell



Electric Automation

Automation specialists

Artikel-Nr.: ICP11I0350000

ICP11I0350000 ELIWELL ICPLUS 902 V/
I-12V

Kaufen von Electric Automation Network



ELEKTRONISCHE STEUERUNG 1 SET POINT (TEMPERATUR , FEUCHTIGKEIT, DRUCK UND ANDEREN MESSGRÖßEN)

ICPlus 902 controllers are one-step electronic devices, used to control temperature. They are compatible with TelevisSystem and with ModBus protocol monitoring systems.

Container PC+ABS UL94 V-0 plastic resin casing, polycarbonat display window, thermoplastic resin buttons

Operating temperature -5...55°C

Storage temperature -30...85°C

Ambient humidity for operation and storage 10...90% RH (non-condensing)

	ICPLUS 902 NTC/ PTC	ICPLUS 902 V/I	ICPLUS 902 TC(J/K), PT100
Display range	probe NTC: -50,0...110,0° Cprobe PTC: -55,0...140,0° C	-99...100 * -99,9...100,0 *999...1000 *	probe Pt100: -150...650° Cprobe TcJ: -40...750° Cprobe TcK: -40...1350°C
Display	decimal point * 3 and a half digits + sign	decimal point * 3 and a half digits + sign	decimal point * 3 and a half digits + sign
Analogue inputs	1 PTC oder NTC *	1 V-I (0...1V,0...5V,0...10V,0...20mA,4...20mA) *	1 Pt100 oder 1 TcJ/TcK
Connections	TTL-port for connection to USB-Unicard, TelevisSystem and systems with ModBus protocol (Needs-Bus- Adapter)	TTL-port for connection to USB-Unicard, TelevisSystem and systems with ModBus protocol (Needs-Bus-Adapter)	TTL-port for connection to USB-Unicard, TelevisSystem and systems with ModBus protocol (Needs-Bus- Adapter)
Digital outputs	1 SPDT 8(4)A 250Va	1 SPDT 8(4)A 250Va	1 SPDT 8(4)A 250Va
Measurement range	from -50 to 140 ° c	from -1999 to 1999	from -150 to 1350 ° C
Power supply	12V~ , 24V~ ,12...24V~/12...36VC (°) ±10%, 50/60Hz115V~/230V~ ±10%, 50/60Hz	12V~ , 24V~ ,12...24V~/12...36VC (°) ±10%, 50/60Hz115V~/230V~ ±10%, 50/60Hz	12V~ , 24V~ ,12...24V~/12...36VC (°) ±10%, 50/60Hz115V~/230V~ ±10%, 50/60Hz
Abmessungen	74 x 32 x 59 mm	74 x 32 x 59 mm	74 x 32 x 59 mm
* wählbar über parameter			

Features

Referenz	ICP1110350000
Modell	CI-PLUS-V/I-12V
Relais	1
Copy Card	Wenn
Humidity Probe	Wenn
Pressure Transducer	Wenn
Versorgungsspannung	12 Vac/vdc
Kompatibilität P	Wenn (Bus Adapter benötigt)

Kompatibilität ModBus

Wenn (Bus Adapter benötigt)

Sonden

1 strom

Format

Panel 74x32

Versorgungsspannung

12 Vac/vdc