


























APPLICAZIONI	CONDUTTORI				CONNETTORI UNIFICATI ENEL					COPPIA MATRICI	
	NATURA	Ø ESTERNO mm	FORMAZIONE n° fili x Ø (mm)	SEZIONE TEORICA mm ²	TIPO	MATRICOLA	ESAGONO DI COMPRESIONE CHIAVE (mm)				
MORSE DI AMARRO PER CONDUTTORI DI ENERGIA 							MORSA				
							ALLUMINIO	ACCIAIO		DERIV.	
							25,5			25,5	M 255 - 520 
								11			M 110 - 520 
							29,5			29,5	M 295 - 520 
								14,5			M 145 - 520 
							34			34	M 340 - 520 
								16			M 160 - 520 
							44			44	M 440 - 520 
								22			M 220 - 520 
							34				M 340 - 520 
								16			M 160 - 520 
										54	M 540 - 520 
							44				M 440 - 520 
	22		M 220 - 520 								
		54	M 540 - 520 								
54			M 540 - 520 								
GIUNTI PER CONDUTTORI DI ENERGIA 							ALLUMINIO	ACCIAIO			
							25,5			M 255 - 520 	
								11		M 110 - 520 	
							29,5			M 295 - 520 	
								14,5		M 145 - 520 	
							34			M 340 - 520 	
								16		M 160 - 520 	
							44			M 440 - 520 	
								22		M 220 - 520 	

 = compressione esagonale