

S802B-B80



S802B-B80 High Performance MCB

General Information

| | |
|-----------------------|--|
| Extended Product Type | S802B-B80 |
| Product ID | 2CCS812001R0805 |
| EAN | 7612271416669 |
| Catalog Description | S802B-B80 High Performance MCB |
| Long Description | <p>The S802B-B80 is a 2-pole High Performance Circuit breaker with B-characteristic, with cage terminal and a rated current of 80 A. It is a current limiting device with a maximum breaking capacity of 16kA at 230/400V. It can be used for voltages up to 230/400V. It has two different tripping mechanisms, the thermal tripping mechanism for overload protection and the electromechanic tripping mechanism for short circuit protection. The S802B-B80 complies with IEC/EN 60947-2 and EN 60898-1 and allows the use for residential, commercial and industrial applications. It has numerous of approvals, therefore it can be used worldwide. The extensive range of accessory makes the use of S802B-B80 more comfortable. Due to the fast arc extinction of S802B-B80 your application will be secured.</p> |

Ordering

| | |
|------------------------|----------|
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85362020 |

Popular Downloads

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 2CCC413003C0208 |
| Instructions and Manuals | 2CCC413016M0008 |

Dimensions

| | |
|----------------------------|---------|
| Product Net Width | 54 mm |
| Product Net Depth / Length | 82.5 mm |
| Product Net Height | 95 mm |
| Product Net Weight | 490 g |

Technical

| | |
|---------------------------|----------------------------------|
| Standards | IEC/EN 60947-2 IEC/EN 60898-1 |
| Number of Poles | 2 |
| Tripping Characteristic | B |
| Rated Current (I_n) | 80 A |
| Rated Operational Voltage | 230/400 V AC |

| | |
|---|--|
| Power Loss | at Rated Operating Conditions per Pole 6.4 W |
| Rated Insulation Voltage (U _i) | 440 V AC |
| Rated Frequency (f) | 50 / 60 Hz |
| Rated Short-Circuit Capacity (I _{cn}) | (230 / 400 V AC) 10 kA |
| Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}) | (230 / 400 V AC) 16 kA (150 V DC) 10 kA |
| Rated Service Short-Circuit Breaking Capacity (I _{cs}) | (230 / 400 V AC) 10 kA |
| Overvoltage Category | III |
| Pollution Degree | 3 |
| Rated Impulse Withstand Voltage (U _{imp}) | 4 kV |
| Housing Material | Insulation group I, RAL 7035 |
| Contact Position Indication | ON / OFF / TRIP |
| Degree of Protection | acc. to IEC 60529 IP20 |
| Remarks | Connection from top and bottom Connecting with CU only IP40 in enclosure with cover Cage terminal with captive screw |
| Terminal Type | Screw Terminals |
| Connecting Capacity | Flexible 1 ... 50 mm ² Stranded 1 ... 70 mm ² |
| Tightening Torque | 3.5 N·m |
| Recommended Screw Driver | Pozidriv 2 |
| Mounting on DIN Rail | TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 |
| Mounting Position | Any |

Environmental

| | |
|-------------------------|--|
| Ambient Air Temperature | Operation -25 ... +60 °C Storage -40 ... +70 °C |
| RoHS Status | Following EU Directive 2011/65/EU |

Certificates and Declarations (Document Number)

| | |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CCC413016D0601 |
| Environmental Information | 2CCY413207D0203 |
| Instructions and Manuals | 2CCC413016M0008 |
| RoHS Information | 2CCC413008D0206 |

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Units | 1 piece |
| Package Level 1 Width | 105 mm |
| Package Level 1 Depth / Length | 60 mm |
| Package Level 1 Height | 99 mm |
| Package Level 1 Gross Weight | 510 g |
| Package Level 1 EAN | 7612271416669 |
| Package Level 2 Units | 1 piece |
| Package Level 2 Height | 0.92 mm |
| Package Level 2 Gross Weight | 0.51 kg |

Classifications

| | |
|----------------------------|--|
| Object Classification Code | F |
| ETIM 4 | EC000042 - Miniature circuit breaker (MCB) |
| ETIM 5 | EC000042 - Miniature circuit breaker (MCB) |
| ETIM 6 | EC000042 - Miniature circuit breaker (MCB) |
| ETIM 7 | EC000042 - Miniature circuit breaker (MCB) |

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → High Performance Circuit Breakers HPCBs

