

PRODUCT-DETAILS

E4.2S/E9 4000 Ekip Touch LSI 4p FHR

E4.2S/E9 4000 Ekip Touch LSI 4p FHR



General Information

| | |
|-----------------------|--|
| Extended Product Type | E4.2S/E9 4000 Ekip Touch LSI 4p FHR |
| Product ID | 1SDA104396R1 |
| EAN | 8056221026215 |
| Catalog Description | E4.2S/E9 4000 Ekip Touch LSI 4p FHR |
| Long Description | C.BREAKER SACE EMAX2 E4.2S 4000 FIXED FOUR-POLE WITH TERMINALS REAR HORIZONTAL AND SOLID-STATE RELEASE IN AC EKIP/TOUCH-LSI R 4000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED 900V |

Ordering

| | |
|------------------------|----------|
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85362090 |

Popular Downloads

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SDC200023D0209 |
| Instructions and Manuals | 1SDH001000R0002 |

Dimensions

| | |
|--------------------|--------|
| Product Net Width | 510 mm |
| Product Net Height | 371 mm |

| | |
|----------------------------|--------|
| Product Net Depth / Length | 270 mm |
| Product Net Weight | 70 kg |

Technical

| | |
|--|--|
| Rated Impulse Withstand Voltage (U_{imp}) | acc. to IEC 60947-2 12 kV |
| Rated Insulation Voltage (U_i) | AC 1000 V |
| Rated Operational Voltage | 900 V AC |
| Rated Short-Circuit Making Capacity (I_{cm}) | (800 V AC) 143 kA (900 V AC) 143 kA |
| Rated Short-time Withstand Current (I_{cw}) | for 1 s 65 kA for 3 s 65 kA |
| Power Loss | 900 W |
| Standards | IEC |
| Number of Poles | 4 |
| Mechanical Durability | 20000 cycle 60 cycles per hour |

Environmental

| | |
|---------------------------|-------------|
| Environmental Information | ROHS, REACH |
|---------------------------|-------------|

Certificates and Declarations (Document Number)

| | |
|-----------------------------------|-----------------|
| Declaration of Conformity - CE | 1SDL000165R0021 |
| Environmental Information | ROHS, REACH |
| Instructions and Manuals | 1SDH001000R0002 |
| Instructions and Manuals (Part 2) | 1SDH001316R0002 |

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Units | 1 piece |
| Package Level 1 Width | 515 mm |
| Package Level 1 Depth / Length | 615 mm |
| Package Level 1 Height | 610 mm |
| Package Level 1 Gross Weight | 81 kg |
| Package Level 1 EAN | 8015644064761 |

Classifications

| | |
|----------------------------|--|
| Object Classification Code | Q |
| ETIM 6 | EC000228 - Power circuit-breaker for trafo/generator/installation prot. |
| ETIM 7 | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| WEEE Category | 4. Large Equipment (Any External Dimension More Than 50 cm) |

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

Low Voltage Products and Systems → Industries → Solar power → 800V AC

