

PRODUCT-DETAILS

ACS580-01-073A-4+B056

LV AC general purpose wall-mounted drive, IEC:
Pn 37 kW, 73 A (ACS580-01-073A-4+B056)



General Information

Global Commercial Alias	ACS580-01-073A-4+B056
Product ID	3AJA0000083574
ABB Type Designation	ACS580-01-073A-4+B056
EAN	6438177306054
Catalog Description	LV AC general purpose wall-mounted drive, IEC: Pn 37 kW, 73 A (ACS580-01-073A-4+B056)

The ACS580-01 is plug-in ready to control your compressors, conveyors, pumps, extruders, centrifuges, mixers, fans and many other variable and constant torque applications, in a variety of light industries, including food and beverage, plastic, textile, material handling, and agriculture.

Long Description

All essential features are built-in as standard, simplifying drive selection, and making additional hardware unnecessary. Versatile and straightforward settings menu and assistants enable fast setup, commissioning, use and maintenance, while rugged and robust design makes it a good fit for various environments. With the ACS580 drives you can easily take full control of your processes to comprehensively manage your plant. The wall-mounted ACS580-01 comes in IP21 enclosure as standard. Also, IP55 and flange mounting units are available.

Ordering

Country of Origin	Finland (FI)
Customs Tariff Number	85044088
Invoice Description	ACS580-01-073A-4+B056 Pn 37 kW I2n 73 A, Protection class IP55, EMC class C2
Made To Order	No
Minimum Order Quantity	1 piece
Order Multiple	1 piece

Quote Only	No
Selling Unit of Measure	piece

Dimensions

Product Net Weight	20 kg
Product Net Depth / Length	265 mm
Product Net Height	685.5 mm
Product Net Width	203 mm
Package Level 1 Depth / Length	760 mm
Package Level 1 Height	428 mm
Package Level 1 Width	298 mm
Package Level 1 Units	1 carton

Technical

Number of Phases	3
Degree of Protection	IP55
Enclosure Type NEMA	Type12
Frequency (f)	50/60 Hz
Frame Size	R4
Input Voltage (U_{in})	380 ... 480 V
Mounting Type	Wall-mounted
Communication Protocol	MODBUS DeviceNet PROFIBUS CAN EtherNet/IP PROFINET IO TCP/IP Other Bus Systems
Number of Hardware Interfaces	Industrial Ethernet 0 PROFINET 0 RS-232 0 RS-422 0 RS-485 1 Serial TTY 0 USB 1 Parallel 2 Other 2
Includes	With control unit Without optical interface With PC connection
Analog Inputs	2
Analog Outputs	2
Number of Digital In/Outputs	6/3
Output Current, Heavy-Duty Use (I_{HD})	61 A
Output Current, Light-Overload Use (I_{LD})	68 A
Output Current, Normal Use (I_n)	73 A
Output Power, Heavy-Duty Use (P_{HD})	30.0 kW
Output Power, Light-Overload Use (P_{LD})	37 kW
Output Power, Normal Use (P_n)	37 kW
Apparent Power Output	51 kV·A

Efficiency Level	IE2
Standby Loss	19 W
Complete Drive Module	
Efficiency (61800-9-2)	

Operating Point Frequency / Current	Absolute Loss	Relative Loss	Efficiency
0 / 25 %	295 W	0.6 %	90.1 %
0 / 50 %	392 W	0.8 %	93.0 %
0 / 100 %	726 W	1.4 %	93.4 %
50 / 25 %	324 W	0.6 %	94.5 %
50 / 50 %	454 W	0.9 %	96.0 %
50 / 100 %	866 W	1.7 %	96.1 %
90 / 50 %	527 W	1.0 %	97.4 %
90 / 100 %	1120 W	2.2 %	97.2 %

Temperature Rating Maximum 40 °C

Additional Information

Product Main Type	ACS580
Product Name	Frequency converter

Classifications

ETIM 7	EC001857 - Frequency converter =< 1 kV
UNSPSC	39122001

Environmental

SCIP	cdc24b2a-20d2-4e65-816b-a638fc9e9fb1 Finland (FI)
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Drives → Low Voltage AC Drives → General Purpose Drives → ACS580-01 - Wall-mounted drive

