

PRODUCT-DETAILS

3GAA093540-BSJ

M3AA 90LD 6



General Information

Product ID	3GAA093540-BSJ
ABB Type Designation	M3AA 90LD 6
Catalog Description	M3AA 90LD 6

Additional Information

ABB Type Designation	M3AA 90LD 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6205-2Z/C3
Bearing NDE	6204-2Z/C3
Country of Origin	Poland (PL) Finland (FI) China (CN)
Customs Tariff Number	85015220
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	1.10 kW	928 r/min	2.66 A	0.770	81.00 %	11.30 N·m	4.00
D	--	50 Hz	230 V	1.10 kW	928 r/min	4.60 A	0.770	81.00 %	11.30 N·m	4.00
Y	--	50 Hz	415 V	1.10 kW	934 r/min	2.52 A	0.750	81.00 %	11.22 N·m	4.30

Gross Weight

22 kg

IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 81.0 % Partial Load (75%) 81.7 % Partial Load (50%) 81.2 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3AA 90LD 6
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	19 kg
Product Type	3AA0__M3AA_AA
Quote Only	No
Replaced Product ID (OLD)	3GAA093614-BSJ
Selling Unit of Measure	piece
Stocked At (Warehouses)	Central Stock Europe Central Stock Spain CSI
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE3 Premium Efficiency Aluminum Motors



