
PRODUCT-DETAILS

3GAA093540-CSK

M3AA 90LD 6



General Information

Product ID	3GAA093540-CSK
ABB Type Designation	M3AA 90LD 6
Catalog Description	M3AA 90LD 6

Additional Information

ABB Type Designation	M3AA 90LD 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6205-2Z/C3
Bearing NDE	6204-2Z/C3
Country of Origin	Finland (FI) Romania (RO)
Customs Tariff Number	85015100
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	0.75 kW	937 r/min	1.78 A	0.760	78.90 %	7.60 N-m	4.60
D	--	50 Hz	230 V	0.75 kW	937 r/min	3.00 A	0.760	78.90 %	7.60 N-m	4.60
Y	--	50 Hz	380 V	0.75 kW	926 r/min	1.86 A	0.780	78.90 %	7.70 N-m	4.30
D	--	50 Hz	220 V	0.75 kW	926 r/min	3.20 A	0.780	78.90 %	7.70 N-m	4.30
Y	--	50 Hz	415 V	0.75 kW	944 r/min	1.75 A	0.740	78.90 %	7.50 N-m	4.90
Y	--	60 Hz	460 V	0.75 kW	1148 r/min	1.56 A	0.730	82.50 %	6.20 N-m	5.10

Gross Weight	22 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 78.9 % Partial Load (75%) 78.8 % Partial Load (50%) 77.0 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 82.5 % Partial Load (75%) 81.9 % Partial Load (50%) 79.6 %
IM Class	IMB14 IM3601
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3AA 90LD 6
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 carton
Pre Modified Motor	3GAA093540-BSK
Product ID	
Product Name	3-Phase squirrel cage motor
Product Net Weight	19 kg
Product Type	3AA3__M3AA_IE3_AA
Quote Only	No
SCIP	27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)
Selling Unit of Measure	piece
Stocked At (Warehouses)	Menden, Germany
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE3 Premium Efficiency Aluminum Motors

