


PRODUCT-DETAILS

3GAA113330-ASK

IE3 Premium Efficiency Aluminum Motor, 2.2 kW, 400 V (3GAA113330-ASK)



General Information

Product ID	3GAA113330-ASK
ABB Type Designation	M3AA 112MC 6
Catalog Description	IE3 Premium Efficiency Aluminum Motor, 2.2 kW, 400 V (3GAA113330-ASK)

Additional Information

ABB Type Designation	M3AA 112MC 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6306-2Z/C3
Bearing NDE	6205-2Z/C3
Connection Configuration	Y
Country of Origin	China (CN) Finland (FI) Poland (PL)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	2.20 kW	967 r/min	5.20 A	0.690	84.30 %	21.70 N·m	6.50
D	--	50 Hz	230 V	2.20 kW	967 r/min	9.00 A	0.690	84.30 %	21.70 N·m	6.50
Y	--	50 Hz	380 V	2.20 kW	962 r/min	5.30 A	0.720	84.30 %	21.80 N·m	6.00
D	--	50 Hz	220 V	2.20 kW	962 r/min	9.10 A	0.720	84.30 %	21.80 N·m	6.00
Y	--	50 Hz	415 V	2.20 kW	970 r/min	5.20 A	0.660	84.30 %	21.60 N·m	6.90
Y	--	60 Hz	460 V	2.20 kW	1172 r/min	4.60 A	0.660	89.50 %	17.90 N·m	7.30

Frame Material	Aluminum
Frame Size	112
Frequency (f)	50 Hz
Gross Weight	48 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 84.3 % Partial Load (75%) 84.7 % Partial Load (50%) 83.2 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 89.5 % Partial Load (75%) 89.6 % Partial Load (50%) 88.4 %
IM Class	IMB3 IM1001
Input Voltage (U _{in})	400 V
Insulation Class	ICLF
Invoice Description	M3AA 112MC 6
IP Class	IP55
Made To Order	No
Medium Description	2.2kW, 6 Poles, Frame Size 112, 3 Phases, 400V, 50Hz, IP55 Enclosure, IMB3/IM1001 Mounting (3GAA113330-ASK)
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Output Power	2.2 kW
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Depth / Length	431 mm
Product Net Height	260 mm
Product Net Weight	43 kg
Product Net Width	222 mm
Product Type	3AA3__M3AA_IE3_AA
Quote Only	No
SCIP	27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)
Selling Unit of Measure	piece
Short Description	2.2kW, 6P, Frame Size 112, 3PH, 400V, 50Hz, IP55, IMB3/IM1001
Stocked At (Warehouses)	Menden, Germany Sant Quirze del Vallés - BCN, Spain Vittuone, Italy
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE3 Premium Efficiency Aluminum Motors

