


PRODUCT-DETAILS

## 3GAA131250-ASK

IE3 Premium Efficiency Aluminum Motor, 11 kW, 400 V (3GAA131250-ASK)



### General Information

Product ID	3GAA131250-ASK
ABB Type Designation	M3AA 132SME 2
Catalog Description	IE3 Premium Efficiency Aluminum Motor, 11 kW, 400 V (3GAA131250-ASK)

### Additional Information

ABB Type Designation	M3AA 132SME 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6308-2Z/C3
Bearing NDE	6206-2Z/C3
Connection Configuration	Y
Country of Origin	Finland (FI) Poland (PL)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	11.00 kW	2922 r/min	19.80 A	0.900	91.20 %	36.00 N-m	10.60
D	--	50 Hz	230 V	11.00 kW	2922 r/min	34.30 A	0.900	91.20 %	36.00 N-m	10.60
Y	--	50 Hz	380 V	11.00 kW	2914 r/min	20.00 A	0.910	91.60 %	35.93 N-m	10.50
D	--	50 Hz	220 V	11.00 kW	2914 r/min	34.60 A	0.910	91.60 %	35.92 N-m	10.40
Y	--	50 Hz	415 V	11.00 kW	2927 r/min	18.60 A	0.890	91.20 %	36.00 N-m	11.30
Y	--	60 Hz	460 V	11.00 kW	3527 r/min	16.70 A	0.890	91.00 %	29.80 N-m	12.10

Frame Material	Aluminum
Frame Size	132
Frequency (f)	50 Hz
Gross Weight	95 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 91.2 % Partial Load (75%) 91.5 % Partial Load (50%) 90.4 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 91.0 % Partial Load (75%) 90.8 % Partial Load (50%) 89.3 %
IM Class	IMB3 IM1001
Input Voltage (U <sub>in</sub> )	400 V
Insulation Class	ICLF
Invoice Description	M3AA 132SME 2
IP Class	IP55
Made To Order	No
Medium Description	11kW, 2 Poles, Frame Size 132, 3 Phases, 400V, 50Hz, IP55 Enclosure, IMB3/IM1001 Mounting (3GAA131250-ASK)
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Output Power	11 kW
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Depth / Length	550 mm
Product Net Height	321 mm
Product Net Weight	90 kg
Product Net Width	262 mm
Product Type	3AA3_M3AA_IE3_AA
Quote Only	No
SCIP	27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)
Selling Unit of Measure	piece
Short Description	11kW, 2P, Frame Size 132, 3PH, 400V, 50Hz, IP55, IMB3/IM1001
Stocked At (Warehouses)	Menden, Germany
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S

---

## Categories

---

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE3 Premium Efficiency Aluminum Motors

