


PRODUCT-DETAILS

3GAA133310-BDJ

M3AA 132MA 6



General Information

Product ID	3GAA133310-BDJ
ABB Type Designation	M3AA 132MA 6
Catalog Description	M3AA 132MA 6

Additional Information

ABB Type Designation	M3AA 132MA 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6208-2Z/C3
Bearing NDE	6206-2Z/C3
Country of Origin	China (CN) Finland (FI) Afghanistan (AF) Poland (PL)
Customs Tariff Number	85015220
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Efficiency Factor	Torque	IS/IN
Y	--	50 Hz	690 V	4.00 kW	964 r/min	5.10 A	0.750	86.80 % 39.10 N·m	4.50
D	--	50 Hz	400 V	4.00 kW	964 r/min	8.90 A	0.750	86.80 % 39.10 N·m	4.50
D	--	50 Hz	415 V	4.00 kW	967 r/min	8.80 A	0.750	86.80 % 39.00 N·m	4.80

Gross Weight	65 kg
--------------	-------

IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 86.8 % Partial Load (75%) 87.7 % Partial Load (50%) 87.0 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3AA 132MA 6
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	60 kg
Product Type	3AA0__M3AA_AA
Quote Only	No
Replaced Product ID (OLD)	3GAA133612-BDJ
Selling Unit of Measure	piece
Stocked At (Warehouses)	Central Stock Europe CSI
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Voltage Code	D
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE3 Premium Efficiency Aluminum Motors

