


PRODUCT-DETAILS

3GAA134300-BDE

IE2 High Efficiency Aluminum Motors, 3 kW, 400 V (3GAA134300-BDE)



General Information

Product ID	3GAA134300-BDE
ABB Type Designation	M3AA 132M 8
Catalog Description	IE2 High Efficiency Aluminum Motors, 3 kW, 400 V (3GAA134300-BDE)

Additional Information

ABB Type Designation	M3AA 132M 8
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6208-2Z/C3
Bearing NDE	6206-2Z/C3
Connection Configuration	D
Country of Origin	Finland (FI) China (CN) Poland (PL)
Customs Tariff Number	85015220
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	3.00 kW	715 r/min	4.90 A	0.640	79.30 %	40.00 N·m	3.20
D	--	50 Hz	400 V	3.00 kW	715 r/min	8.50 A	0.640	79.30 %	40.00 N·m	3.20
D	--	60 Hz	460 V	3.00 kW	865 r/min	6.80 A	0.680	81.00 %	33.10 N·m	3.20

Frame Material	Aluminum
Frame Size	132
Frequency (f)	50 Hz

Gross Weight	58 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE1 Full Load (100%) 79.3 % Partial Load (75%) 78.8 % Partial Load (50%) 75.5 %
IE Class Data (60 Hz)	IE Class IE1 Full Load (100%) 81.0 % Partial Load (75%) 81.8 % Partial Load (50%) 79.8 %
IM Class	IMB5 IM3001
Input Voltage (U _{in})	400 V
Insulation Class	ICLF
Invoice Description	M3AA 132M 8
IP Class	IP55
Made To Order	No
Medium Description	3kW, 8 Poles, Frame Size 132, 3 Phases, 400V, 50Hz, IP55 Enclosure, IMB5/IM3001 Mounting (3GAA134300-BDE)
Minimum Order Quantity	1 piece
Number of Poles (High)	8
Order Multiple	1 piece
Output Power	3 kW
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Depth / Length	487 mm
Product Net Height	296 mm
Product Net Weight	53 kg
Product Net Width	262 mm
Product Type	3AA2 M3AA IE2 AA
Quote Only	No
Replaced Product ID (OLD)	3GAA134062-BDA 3GAA134002-BDE
SCIP	27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)
Selling Unit of Measure	piece
Short Description	3kW, 8P, Frame Size 132, 3PH, 400V, 50Hz, IP55, IMB5/IM3001
Stocked At (Warehouses)	Menden, Germany Shanghai, China
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Aluminum Motors

