

PRODUCT-DETAILS

3GAA163420-ADK

IE3 Premium Efficiency Aluminum Motor, 11 kW, 400 V (3GAA163420-ADK)



General Information

Product ID	3GAA163420-ADK
ABB Type Designation	M3AA 160MLB 6
Catalog Description	IE3 Premium Efficiency Aluminum Motor, 11 kW, 400 V (3GAA163420-ADK)

Additional Information

ABB Type Designation	M3AA 160MLB 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6309-2Z/C3
Bearing NDE	6209-2Z/C3
Connection Configuration	D
Country of Origin	Poland (PL) Finland (FI) China (CN)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	11.00 kW	979 r/min	13.60 A	0.740	90.30 %	107.00 N-m	8.50
D	--	50 Hz	400 V	11.00 kW	979 r/min	23.50 A	0.740	90.30 %	107.00 N-m	8.50
Y	--	50 Hz	660 V	11.00 kW	976 r/min	13.80 A	0.770	90.30 %	107.00 N-m	7.90
D	--	50 Hz	380 V	11.00 kW	976 r/min	23.80 A	0.770	90.30 %	107.00 N-m	7.90
D	--	50 Hz	415 V	11.00 kW	981 r/min	23.60 A	0.710	90.30 %	107.00 N-m	8.80
D	--	60 Hz	460 V	11.00 kW	1183 r/min	20.60 A	0.730	91.70 %	88.70 N-m	9.40

Frame Material	Aluminum
Frame Size	160
Frequency (f)	50 Hz
Gross Weight	149 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 90.3 % Partial Load (75%) 90.4 % Partial Load (50%) 89.2 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 91.7 % Partial Load (75%) 91.8 % Partial Load (50%) 90.5 %
IM Class	IMB3 IM1001
Input Voltage (U _{in})	400 V
Insulation Class	ICLF
Invoice Description	M3AA 160MLB 6
IP Class	IP55
Made To Order	No
Medium Description	11kW, 6 Poles, Frame Size 160, 3 Phases, 400V, 50Hz, IP55 Enclosure, IMB3/IM1001 Mounting (3GAA163420-ADK)
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Output Power	11 kW
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Depth / Length	681 mm
Product Net Height	370 mm
Product Net Weight	139 kg
Product Net Width	310 mm
Product Type	3AA3 M3AA IE3 AA
Quote Only	No
Replaced Product ID (OLD)	3GAA163052-ADK
SCIP	27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)
Selling Unit of Measure	piece
Short Description	11kW, 6P, Frame Size 160, 3PH, 400V, 50Hz, IP55, IMB3/IM1001
Stocked At (Warehouses)	Menden, Germany Sant Quirze del Vallés - BCN, Spain
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE3 Premium Efficiency Aluminum Motors

