


PRODUCT-DETAILS

3GAA183420-BDK

IE3 Premium Efficiency Aluminum Motor, 18.5 kW, 400 V (3GAA183420-BDK)



General Information

Product ID	3GAA183420-BDK
ABB Type Designation	M3AA 180MLB 6
Catalog Description	IE3 Premium Efficiency Aluminum Motor, 18.5 kW, 400 V (3GAA183420-BDK)

Additional Information

ABB Type Designation	M3AA 180MLB 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6310-2Z/C3
Bearing NDE	6209-2Z/C3
Connection Configuration	D
Country of Origin	Finland (FI) China (CN) Poland (PL)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	18.50 kW	980 r/min	23.30 A	0.720	91.70 %	179.50 N-m	6.80
D	--	50 Hz	400 V	18.50 kW	980 r/min	40.30 A	0.720	91.70 %	179.50 N-m	6.80
Y	--	50 Hz	660 V	18.50 kW	978 r/min	23.90 A	0.740	91.70 %	179.86 N-m	6.20
D	--	50 Hz	380 V	18.50 kW	978 r/min	41.40 A	0.740	91.70 %	179.86 N-m	6.20
D	--	50 Hz	415 V	18.50 kW	982 r/min	40.50 A	0.690	91.70 %	179.16 N-m	7.10
D	--	60 Hz	460 V	18.50 kW	1183 r/min	36.10 A	0.690	93.00 %	149.00 N-m	8.20

Frame Material	Aluminum
Frame Size	180
Frequency (f)	50 Hz
Gross Weight	178 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 91.7 % Partial Load (75%) 91.9 % Partial Load (50%) 91.0 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 93.0 % Partial Load (75%) 93.0 % Partial Load (50%) 92.1 %
IM Class	IMB5 IM3001
Input Voltage (U _{in})	400 V
Insulation Class	ICLF
Invoice Description	M3AA 180MLB 6
IP Class	IP55
Made To Order	No
Medium Description	18.5kW, 6 Poles, Frame Size 180, 3 Phases, 400V, 50Hz, IP55 Enclosure, IMB5/IM3001 Mounting (3GAA183420-BDK)
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Output Power	18.5 kW
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Depth / Length	726 mm
Product Net Height	405 mm
Product Net Weight	168 kg
Product Net Width	341 mm
Product Type	3AA3_M3AA_IE3_AA
Quote Only	No
Replaced Product ID (OLD)	3GAA183054-BDK
SCIP	27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)
Selling Unit of Measure	piece
Short Description	18.5kW, 6P, Frame Size 180, 3PH, 400V, 50Hz, IP55, IMB5/IM3001
Stocked At (Warehouses)	Menden, Germany
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1

UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE3 Premium Efficiency Aluminum Motors

