

PRODUCT-DETAILS

3GAA201430-ADG

(3GAA201430-ADG)



General Information

Product ID	3GAA201430-ADG
ABB Type Designation	M3AA 200MLC 2
Catalog Description	(3GAA201430-ADG)

Additional Information

ABB Type Designation	M3AA 200MLC 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6312-2Z/C3
Bearing NDE	6210-2Z/C3
Country of Origin	Finland (FI) Poland (PL)
Customs Tariff Number	85015290
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	45.00 kW	2957 r/min	45.90 A	0.880	93.30 %	145.00 N-m	8.10
Y	--	50 Hz	690 V	45.00 kW	2957 r/min	45.90 A	0.880	93.30 %	145.00 N-m	8.10
Y	--	50 Hz	690 V	45.00 kW	2957 r/min	45.90 A	0.880	93.30 %	145.00 N-m	8.10
Y	--	50 Hz	690 V	45.00 kW	2957 r/min	45.90 A	0.880	93.30 %	145.00 N-m	8.10
Y	--	50 Hz	690 V	45.00 kW	2957 r/min	45.90 A	0.880	93.30 %	145.00 N-m	8.10
Y	--	50 Hz	690 V	45.00 kW	2957 r/min	45.90 A	0.880	93.30 %	145.00 N-m	8.10
D	--	50 Hz	400 V	45.00 kW	2957 r/min	79.10 A	0.880	93.30 %	145.00 N-m	8.10
D	--	50 Hz	400 V	45.00 kW	2957 r/min	79.10 A	0.880	93.30 %	145.00 N-m	8.10
D	--	50 Hz	400 V	45.00 kW	2957 r/min	79.10 A	0.880	93.30 %	145.00 N-m	8.10
D	--	50 Hz	400 V	45.00 kW	2957 r/min	79.10 A	0.880	93.30 %	145.00 N-m	8.10
D	--	50 Hz	400 V	45.00 kW	2957 r/min	79.10 A	0.880	93.30 %	145.00 N-m	8.10
D	--	50 Hz	400 V	45.00 kW	2957 r/min	79.10 A	0.880	93.30 %	145.00 N-m	8.10
D	--	50 Hz	415 V	45.00 kW	2960 r/min	77.00 A	0.870	93.40 %	145.00 N-m	8.50
D	--	50 Hz	415 V	45.00 kW	2960 r/min	77.00 A	0.870	93.40 %	145.00 N-m	8.50
D	--	50 Hz	415 V	45.00 kW	2960 r/min	77.00 A	0.870	93.40 %	145.00 N-m	8.50
D	--	50 Hz	415 V	45.00 kW	2960 r/min	77.00 A	0.870	93.40 %	145.00 N-m	8.50
D	--	50 Hz	415 V	45.00 kW	2960 r/min	77.00 A	0.870	93.40 %	145.00 N-m	8.50
D	--	50 Hz	415 V	45.00 kW	2960 r/min	77.00 A	0.870	93.40 %	145.00 N-m	8.50
D	--	60 Hz	440 V	45.00 kW	3559 r/min	71.10 A	0.890	93.30 %	120.00 N-m	8.50
D	--	60 Hz	440 V	45.00 kW	3559 r/min	71.10 A	0.890	93.30 %	120.00 N-m	8.50
D	--	60 Hz	440 V	45.00 kW	3559 r/min	71.10 A	0.890	93.30 %	120.00 N-m	8.50
D	--	60 Hz	440 V	45.00 kW	3559 r/min	71.10 A	0.890	93.30 %	120.00 N-m	8.50
D	--	60 Hz	440 V	45.00 kW	3559 r/min	71.10 A	0.890	93.30 %	120.00 N-m	8.50
D	--	60 Hz	440 V	45.00 kW	3559 r/min	71.10 A	0.890	93.30 %	120.00 N-m	8.50
D	--	60 Hz	460 V	45.00 kW	3563 r/min	68.70 A	0.880	93.40 %	120.00 N-m	9.20
D	--	60 Hz	460 V	45.00 kW	3563 r/min	68.70 A	0.880	93.40 %	120.00 N-m	9.20
D	--	60 Hz	460 V	45.00 kW	3563 r/min	68.70 A	0.880	93.40 %	120.00 N-m	9.20
D	--	60 Hz	460 V	45.00 kW	3563 r/min	68.70 A	0.880	93.40 %	120.00 N-m	9.20
D	--	60 Hz	460 V	45.00 kW	3563 r/min	68.70 A	0.880	93.40 %	120.00 N-m	9.20

Frame Material Aluminum

Frame Size 200

Gross Weight 235 kg

IC Class IC411

IE Class Data (50 Hz) IE Class IE2
 Full Load (100%) 93.3 %
 Partial Load (75%) 93.8 %
 Partial Load (50%) 93.2 %

IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 93.3 % Partial Load (75%) 93.3 % Partial Load (50%) 92.3 %
IM Class	IMB3 IM1001
Insulation Class	ICLF
Invoice Description	M3AA 200MLC 2
IP Class	IP55
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	225 kg
Product Type	3AA2_M3AA_IE2_AA
Quote Only	No
Replaced Product ID (OLD)	3GAA201033-ADG
SCIP	27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)
Selling Unit of Measure	piece
Stocked At (Warehouses)	Menden, Germany
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Aluminum Motors

