

PRODUCT-DETAILS

3GAA202410-BDK

IE3 Premium Efficiency Aluminum Motor, 30 kW, 400 V (3GAA202410-BDK)



General Information

Product ID	3GAA202410-BDK
ABB Type Designation	M3AA 200MLA 4
Catalog Description	IE3 Premium Efficiency Aluminum Motor, 30 kW, 400 V (3GAA202410-BDK)

Additional Information

ABB Type Designation	M3AA 200MLA 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6312-2Z/C3
Bearing NDE	6210-2Z/C3
Connection Configuration	D
Country of Origin	Poland (PL) Finland (FI)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	30.00 kW	1481 r/min	31.90 A	0.840	93.60 %	193.44 N-m	7.40
D	--	50 Hz	400 V	30.00 kW	1481 r/min	55.10 A	0.840	93.60 %	193.42 N-m	7.50
Y	--	50 Hz	660 V	30.00 kW	1478 r/min	33.10 A	0.850	93.60 %	193.80 N-m	6.80
D	--	50 Hz	380 V	30.00 kW	1478 r/min	57.40 A	0.850	93.60 %	193.82 N-m	6.70
D	--	50 Hz	415 V	30.00 kW	1483 r/min	53.70 A	0.830	93.60 %	193.22 N-m	8.00
D	--	60 Hz	460 V	30.00 kW	1783 r/min	48.20 A	0.830	94.10 %	160.63 N-m	8.50

Frame Material	Aluminum
Frame Size	200
Frequency (f)	50 Hz
Gross Weight	256 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 93.6 % Partial Load (75%) 93.8 % Partial Load (50%) 93.1 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 94.1 % Partial Load (75%) 94.0 % Partial Load (50%) 93.0 %
IM Class	IMB5 IM3001
Input Voltage (U _{in})	400 V
Insulation Class	ICLF
Invoice Description	M3AA 200MLA 4
IP Class	IP55
Made To Order	No
Medium Description	30kW, 4 Poles, Frame Size 200, 3 Phases, 400V, 50Hz, IP55 Enclosure, IMB5/IM3001 Mounting (3GAA202410-BDK)
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Output Power	30 kW
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Depth / Length	821 mm
Product Net Height	532 mm
Product Net Weight	246 kg
Product Net Width	380 mm
Product Type	3AA3_M3AA_IE3_AA
Quote Only	No
Replaced Product ID (OLD)	3GAA202051-BDK
SCIP	27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)
Selling Unit of Measure	piece
Short Description	30kW, 4P, Frame Size 200, 3PH, 400V, 50Hz, IP55, IMB5/IM3001
Stocked At (Warehouses)	Menden, Germany Sant Quirze del Vallés - BCN, Spain
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1

UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE3 Premium Efficiency Aluminum Motors

