


PRODUCT-DETAILS

3GAA203410-ADL

M3AA 200MLA 6



General Information

Product ID	3GAA203410-ADL
ABB Type Designation	M3AA 200MLA 6
Catalog Description	M3AA 200MLA 6

Additional Information

ABB Type Designation	M3AA 200MLA 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6312-2Z/C3
Bearing NDE	6209-2Z/C3
Country of Origin	Finland (FI) Poland (PL)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Efficiency Factor	Torque	IS/IN
Y	--	50 Hz	690 V	18.50 kW	980 r/min	22.50 A	0.750 91.70 %	180.27 N·m	6.40
D	--	50 Hz	400 V	18.50 kW	980 r/min	38.80 A	0.750 91.70 %	180.27 N·m	6.40
D	--	50 Hz	415 V	18.50 kW	982 r/min	38.90 A	0.720 91.70 %	179.90 N·m	6.90
D	--	60 Hz	440 V	18.50 kW	1181 r/min	34.30 A	0.760 93.00 %	149.59 N·m	7.10
D	--	60 Hz	460 V	18.50 kW	1183 r/min	34.20 A	0.730 93.00 %	149.33 N·m	7.40

Gross Weight	187 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 91.7 % Partial Load (75%) 92.2 % Partial Load (50%) 91.5 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 93.0 % Partial Load (75%) 93.0 % Partial Load (50%) 91.9 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3AA 200MLA 6
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	177 kg
Product Type	5AA3 _M3AA_IE3_AA
Quote Only	No
Replaced Product ID (OLD)	3GAA203051-ADL
Selling Unit of Measure	piece
Stocked At (Warehouses)	Central Stock Europe Central Stock Spain
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE3 Premium Efficiency Aluminum Motors

