

PRODUCT-DETAILS

3GAA203410-BDL

IE3 Premium Efficiency Aluminum Motor, 18.5 kW, 400 V (3GAA203410-BDL)



General Information

Product ID	3GAA203410-BDL
ABB Type Designation	M3AA 200MLA 6
Catalog Description	IE3 Premium Efficiency Aluminum Motor, 18.5 kW, 400 V (3GAA203410-BDL)

Additional Information

ABB Type Designation	M3AA 200MLA 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6312-2Z/C3
Bearing NDE	6209-2Z/C3
Connection Configuration	D
Country of Origin	Finland (FI) Poland (PL)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	18.50 kW	980 r/min	22.50 A	0.750	91.70 %	180.27 N-m	6.40
D	--	50 Hz	400 V	18.50 kW	980 r/min	38.80 A	0.750	91.70 %	180.27 N-m	6.40
D	--	50 Hz	415 V	18.50 kW	982 r/min	38.90 A	0.720	91.70 %	179.90 N-m	6.90
D	--	60 Hz	440 V	18.50 kW	1181 r/min	34.30 A	0.760	93.00 %	149.59 N-m	7.10
D	--	60 Hz	460 V	18.50 kW	1183 r/min	34.20 A	0.730	93.00 %	149.33 N-m	7.40

Frame Material	Aluminum
Frame Size	200
Frequency (f)	50 Hz
Gross Weight	187 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 91.7 % Partial Load (75%) 92.2 % Partial Load (50%) 91.5 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 93.0 % Partial Load (75%) 93.0 % Partial Load (50%) 91.9 %
IM Class	IMB5 IM3001
Input Voltage (U _{in})	400 V
Insulation Class	ICLF
Invoice Description	M3AA 200MLA 6
IP Class	IP55
Made To Order	No
Medium Description	18.5kW, 6 Poles, Frame Size 200, 3 Phases, 400V, 50Hz, IP55 Enclosure, IMB5/IM3001 Mounting (3GAA203410-BDL)
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Output Power	18.5 kW
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Depth / Length	726 mm
Product Net Height	425 mm
Product Net Weight	177 kg
Product Net Width	382 mm
Product Type	5AA3__M3AA_IE3_AA
Quote Only	No
Replaced Product ID (OLD)	3GAA203051-BDL
SCIP	27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)
Selling Unit of Measure	piece
Short Description	18.5kW, 6P, Frame Size 200, 3PH, 400V, 50Hz, IP55, IMB5/IM3001
Stocked At (Warehouses)	Menden, Germany
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D

WEEE Category

4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE3 Premium Efficiency Aluminum Motors

