


PRODUCT-DETAILS

3GAA222210-ADK

M3AA 225SMA 4



General Information

Product ID	3GAA222210-ADK
ABB Type Designation	M3AA 225SMA 4
Catalog Description	M3AA 225SMA 4

Additional Information

ABB Type Designation	M3AA 225SMA 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6313-2Z/C3
Bearing NDE	6212-2Z/C3
Country of Origin	Finland (FI) Poland (PL)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Efficiency Factor	Torque	IS/IN
Y	--	50 Hz	690 V	37.00 kW	1482 r/min	39.80 A	0.830 93.90 %	238.60 N·m	7.20
D	--	50 Hz	400 V	37.00 kW	1482 r/min	68.90 A	0.830 93.90 %	238.60 N·m	7.20
Y	--	50 Hz	660 V	37.00 kW	1477 r/min	40.80 A	0.850 93.90 %	239.10 N·m	6.50
D	--	50 Hz	380 V	37.00 kW	1477 r/min	71.20 A	0.850 93.90 %	239.10 N·m	6.50
D	--	50 Hz	415 V	37.00 kW	1483 r/min	67.70 A	0.810 93.90 %	238.38 N·m	7.60
D	--	60 Hz	460 V	37.00 kW	1783 r/min	59.30 A	0.830 94.50 %	198.12 N·m	8.80

Gross Weight	325 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 93.9 % Partial Load (75%) 93.9 % Partial Load (50%) 93.4 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 94.5 % Partial Load (75%) 94.7 % Partial Load (50%) 94.1 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3AA 225SMA 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	315 kg
Product Type	3AA3__M3AA_IE3_AA
Quote Only	No
Replaced Product ID (OLD)	3GAA222051-ADK
Selling Unit of Measure	piece
Stocked At (Warehouses)	Central Stock Europe
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE3 Premium Efficiency Aluminum Motors

