

PRODUCT-DETAILS

# 3GAA253220-ADK

## IE3 Premium Efficiency Aluminum Motor, 45 kW, 400 V (3GAA253220-ADK)




---

### General Information

Product ID	3GAA253220-ADK
ABB Type Designation	M3AA 250SMB 6
Catalog Description	IE3 Premium Efficiency Aluminum Motor, 45 kW, 400 V (3GAA253220-ADK)

---

### Additional Information

ABB Type Designation	M3AA 250SMB 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6315-2Z/C3
Bearing NDE	6213-2Z/C3
Connection Configuration	D
Country of Origin	Finland (FI) Poland (PL)
Customs Tariff Number	85015290
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	45.00 kW	991 r/min	50.40 A	0.790	93.70 %	433.20 N-m	8.00
D	--	50 Hz	400 V	45.00 kW	991 r/min	87.30 A	0.790	93.70 %	433.20 N-m	8.00
Y	--	50 Hz	660 V	45.00 kW	990 r/min	51.90 A	0.810	93.70 %	433.67 N-m	7.40
D	--	50 Hz	380 V	45.00 kW	990 r/min	89.80 A	0.810	93.70 %	433.67 N-m	7.40
D	--	50 Hz	415 V	45.00 kW	991 r/min	87.50 A	0.760	93.70 %	433.01 N-m	8.40
D	--	60 Hz	460 V	45.00 kW	1193 r/min	77.50 A	0.770	94.50 %	361.70 N-m	8.30

Frame Material	Aluminum
Frame Size	250
Frequency (f)	50 Hz
Gross Weight	399 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 93.7 % Partial Load (75%) 93.7 % Partial Load (50%) 92.7 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 94.5 % Partial Load (75%) 94.4 % Partial Load (50%) 93.4 %
IM Class	IMB3 IM1001
Input Voltage (U <sub>in</sub> )	400 V
Insulation Class	ICLF
Invoice Description	M3AA 250SMB 6
IP Class	IP55
Made To Order	No
Medium Description	45kW, 6 Poles, Frame Size 250, 3 Phases, 400V, 50Hz, IP55 Enclosure, IMB3/IM1001 Mounting (3GAA253220-ADK)
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Output Power	45 kW
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Depth / Length	884 mm
Product Net Height	601 mm
Product Net Weight	389 kg
Product Net Width	473 mm
Product Type	3AA3__M3AA_IE3_AA
Quote Only	No
Replaced Product ID (OLD)	3GAA253052-ADK
SCIP	27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)
Selling Unit of Measure	piece
Short Description	45kW, 6P, Frame Size 250, 3PH, 400V, 50Hz, IP55, IMB3/IM1001
Stocked At (Warehouses)	Menden, Germany
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

---

## Categories

---

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE3 Premium Efficiency Aluminum Motors

